

Citation for published version:
Bimbo, NM, Sharpe, J, Noguera Diaz, AN, Physick, A, Holyfield, L, Rowlandson, J, Xu, W, Ladha, A, Ting, V & Mays, TJ 2014, 'Fuel Gas Storage: The Challenge of Hydrogen', ChemEngDayUK 2014, Manchester, UK United Kingdom, 7/04/14 - 8/04/14.

Link to publication

Publication date:

2014

University of Bath

Alternative formats

If you require this document in an alternative format, please contact: openaccess@bath.ac.uk

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

Take down policyIf you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Download date: 09. Mar. 2023

Fuel Gas Storage – The Challenge of Hydrogen

Nuno Bimbo, Jessica Sharpe, Antonio Noguera-Diaz, Andrew Physick, Leighton Holyfield, Jemma Rowlandson, Wesley Xu, Abbas Ladha, Valeska Ting and Timothy Mays.

- •URL: http://people.bath.ac.uk/cestjm; : http://people.bath.ac.uk/vt233
- Department of Chemical Engineering, University of Bath, UK
- ·Centre for Doctoral Training in Sustainable Chemical Technologies, University of Bath, UK

Clean energy

chain

Hydrogen

Global issue

- Increasing demand for energy
 - Population growth
 - Increasing wealth per capita
- Demand for new sources of energy Global warming and air quality
 - Depletion of fossil fuels

Solution:

Using hydrogen as a clean energy vector!

Benefits:

- Highest energy content of any chemical fuel on a mass basis
- Abundant in the form of water, biomass or hydrocarbons
- If combusted or used in a fuel cell with pure oxygen, its only product is water
- Can be used as a wide-scale clean energy vector

Hydrogen storage

Problem:


- Hydrogen has a very low density
- Conventional methods of increasing the density is to compress or liquefy
- BUT, these require unfavourable conditions.





Examples of compression and liquefaction H₂ tanks

Solution:

Adsorb the hydrogen inside nanoporous materials!







Materials Hydrogen Storage in Porous Materials Analysis

We synthesise, characterise, analyse and model a variety of different types of nanoporous materials including:

- Metal-organic frameworks
- Polymers of intrinsic microporosity
- Activated carbons
- Zeolites


Example synthesis: ZIF-12


Synthetic route:

Ammonia $(CH_3COO)_2Co \cdot 4H_2O + BIM \longrightarrow Co(PhIM)_2$

Toluene









ZIF-12 XRD. Red: experimental data; Black: from CIF file

Inelastic neutron scattering

We used inelastic neutron scattering as it allowed for the verification of our model






INS integrated elastic peak and spectra for TE7

Kinetics

We have studied the kinetics of hydrogen adsorption for some carbons and shown that the mass transfer coefficients follow an Arrhenius relationship

Computer simulations

We use computer simulations in order to verify our model, and to study the molecular dynamics of the system



• AX-21

Arrhenius plot of mass transfer coefficients as a function of temperature

Systems


Analysis

We do the analysis and modelling of excess isotherms, in order to compare with alternative storage methods, and to study the fundamentals of the adsorption process.

$m_{\rm E} = (\rho_{\rm A} - \rho_{\rm B}) V_{\rm P} \theta_{\rm A}$

- $m_{\rm F}$ = excess uptake ρ_A = adsorbate density
- $\rho_{\rm B}$ = bulk density V_P = pore volume
- Θ_A = fill factor

The analysis allows us \S^1 to determine the optimum conditions for physisorption



Experimental high-pressure hydrogen excess and fitted isotherms for AX-21

- FIUIII ulese calculations we are able to produce design curves, which compare the amount of hydrogen stored via adsorption vs. the amount stored via compression at the same conditions.
- We found that there is a critical pressure, above which compression always stores more hydrogen than adsorption.

 The analysis has been expanded to calculate the amount of hydrogen stored in tanks containing varying quantities of adsorbent, at any pressure or temperature.

 $(1000/RT) / mol kJ^{-1}$

