

Pump Repair

API RECOMMENDED PRACTICE 697
FIRST EDITION, APRIL 2023



American
Petroleum
Institute

Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. Every effort has been made by the Institute to ensure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be utilized. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

All rights reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher. Contact the Publisher, API Publishing Services, 200 Massachusetts Avenue, NW, Washington, DC 20001.

Copyright © 2023 American Petroleum Institute

Foreword

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

The verbal forms used to express the provisions in this specification are as follows:

- the term “shall” denotes a minimum requirement in order to conform to the standard;
- the term “should” denotes a recommendation or that which is advised but not required in order to conform to the standard;
- the term “may” denotes a course of action permissible within the limits of a standard;
- the term “can” is used to express possibility or capability.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 200 Massachusetts Avenue, NW, Washington, DC 20001. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually by API, 200 Massachusetts Avenue, NW, Washington, DC 20001.

Suggested revisions are invited and should be submitted to the Standards Department, API, 200 Massachusetts Avenue, NW, Washington, DC 20001, standards@api.org.

Contents

Page

1	Scope and General Recommendations and Information.....	1
1.1	Scope	1
1.2	General Recommendations	1
1.3	Alternative Procedures	1
1.4	Conflicting Requirements	1
1.5	Statutory Requirements	2
1.6	Unit Responsibility	2
1.7	Selection of a Repair Shop	2
1.8	Communication.....	2
2	Normative References	3
3	Terms, Definitions, Acronyms, and Abbreviations	5
3.1	Terms and Definitions	5
3.2	Acronyms and Abbreviations	10
4	Inspection of Installed Pump and Removal from Baseplate	12
4.1	Scope	12
4.2	Obtaining Data	12
4.3	Preparations for Pump Shutdown.....	13
4.4	Inspections After Shutdown	13
4.5	Pump Removal Considerations.....	15
4.6	Removing Pump from Baseplate	15
4.7	BB5 Inner Bundle Removal.....	17
4.8	Discussion of Work Scope with Repair Shop.....	17
5	Field Inspections (Following Pump Removal from Baseplate).....	17
5.1	General	17
5.2	Pump Driver.....	18
5.3	Gearbox	19
5.4	Coupling Components	19
5.5	Baseplates	19
5.6	Foundation	20
5.7	Auxiliary Systems.....	21
5.8	Guards for Exposed Shaft Areas	26
5.9	Work Scopes and Revised Work Scopes.....	27
6	Field Repair	27
6.1	General	27
6.2	Work Scopes	27
6.3	Foundation.....	27
6.4	Grouting	27
6.5	Baseplates	27
6.6	Pump Driver.....	28
6.7	Gearbox	28
6.8	Coupling and Exposed Shaft Guards	28
6.9	Auxiliary Systems.....	28
6.10	Electrical Grounding	28
6.11	Piping Strain.....	28
7	Shipment of Equipment or Components to or from Repair Shop	28

7.1	Preparation for Shipment	28
7.2	Shipment.....	30
7.3	Shipping Containers/Skids	30
8	Receipt of Pump and Components by Repair Shop	32
8.1	Receiving of Pump	32
8.2	Receiving Inspections.....	32
9	Disassembly and Cleaning of the Pump (in Repair Shop)	33
9.1	Disassembly of the Pump	33
9.2	Cleaning Methods and Precautions.....	37
10	Shop Inspection of Disassembled Pump, Components, and Casing	37
10.1	General	37
10.2	Additional Inspection, Evaluation, and Possible Disassembly of Assembled Rotor [9.1.4 c) and 9.1.4 e) for Volute-style Rotors].....	50
10.3	Rotor Component Inspections	52
10.4	Stationary and Pressure Casing Components Inspections	62
10.5	Bearings and Bearing Housing Assembly Inspection.....	75
10.6	Auxiliary Items	79
10.7	Inspection Report of Components and Evaluation of Rotor Component Inspection Data.....	81
11	Pump Modification and Rerates	84
11.1	General.....	84
11.2	Pump Type Conversions.....	86
11.3	Changes to Alter Pump Hydraulics (Flow, Head, Efficiency, NPSH3, Performance Curve Shape)	88
11.4	Changes to Reduce Hydraulic Disturbances.....	97
11.5	Mechanical Changes	101
11.6	Mechanical Seal and Seal System Changes	117
11.7	Material Changes	118
11.8	Accessory Changes	120
11.9	Performance Testing After Making Changes (Modifications)	122
12	Repair Processes and New Component Manufacture	122
12.1	General	122
12.2	Wear Ring Repairs	124
12.3	Rotating Assembly Component Repairs.....	133
12.4	Stationary Component Repairs.....	139
12.5	Auxiliary Items (As Appropriate).....	151
12.6	Replacement Components	152
13	Rotor Assembly and Balancing.....	153
13.1	General	153
13.2	Low-speed Component Balancing.....	155
13.3	Assembly and Balancing	158
13.4	Residual Unbalance Testing.....	165
13.5	Installation of Trim Parts and Coupling Hub	165
13.6	Balancing Equipment and Documentation	165
14	Shop Assembly of Pump	166
14.1	General	166
14.2	Preparation for Pump Assembly (All Pumps).....	166
14.3	Final Assembly—General (All Pumps)	168
14.4	OH1, OH2, OH3, and Two-stage OH (Final Assembly).....	176
14.5	OH1, OH2, and OH3 (Specific Final Assembly)	177
14.6	Driver Stand and Motor Installation—OH3 Only.....	180
14.7	OH4 (Specific Final Assembly).....	181

14.8 OH5 (Specific Final Assembly).....	185
14.9 BB (Final Assembly General)	186
14.10 BB1 (Specific Final Assembly).....	195
14.11 BB2 (Specific Final Assembly).....	198
14.12 BB3 (Specific Final Assembly).....	199
14.13 BB4 (Specific Final Assembly).....	199
14.14 BB5 (Specific Final Assembly).....	201
14.15 Final Accessory Assembly—General (All Pumps).....	206
14.16 Tagging.....	208
14.17 Paint	209
14.18 Shipping Preparation	209
15 Shipment of Equipment or Components from Repair Shop	209
16 Documentation.....	210
16.1 Repair Shop Documentation.....	210
16.2 Owner Documentation	210
17 Receipt of Repaired Pump by Owner	210
17.1 Initial Receipt Review.....	210
17.2 Detailed Receipt Review	210
18 Reinstallation of Pump and Systems in Field.....	212
18.1 General.....	212
18.2 Prior to Field Installation of Pump	212
18.3 Transport from Repair Shop or Warehouse to Field.....	213
18.4 Field Installation.....	213
18.5 Final Checks (As Applicable to the Particular Pump).....	216
19 Start-up	216
19.1 Scope.....	216
19.2 Process Pump Pre-start Checks	217
19.3 Placing Pump Back into Service.....	217
19.4 Post-start-up Checks.....	218
19.5 Pump Monitoring	218
Annex A (informative) Pump Designations and Descriptions	A-1
Annex B (informative) Pump Problem Resolution Process.....	B-1
Annex C (informative) Equipment and Process Information.....	C-1
Annex D (informative) NDT Methods.....	D-1
Annex E (informative) Total Indicator Reading	E-1
Annex F (informative) Rolling Element Bearings.....	F-1
Annex G (informative) Examples of Rolling Element Bearing Damage.....	G-1
Annex H (informative) Hydrodynamic Bearings	H-1
Annex I (informative) Examples of Hydrodynamic Bearing Damage.....	I-1
Annex J (informative) Material Combinations—Galling Resistance.....	J-1
Annex K (informative) Impeller Measuring	K-1
Annex L (informative) Coatings and Overlays for Pumps	L-1
Annex M (informative) Weld Repair Flowcharts.....	M-1
Annex N (informative) Nonmetallic Components	N-1

Annex O (informative) O-ring Information	O-1
Annex P (informative) Coatings and Overlays for Pumps	P-1
Annex Q (informative) Procedure for the Verification of Residual Unbalance	Q-1
Annex R (informative) Pressure Assembly Leak Test.....	R-1
Annex S (informative) Torque Values, Cap Screw and Stud Identification.....	S-1
Annex T (informative) Keys and Keyways	T-1
Annex U (informative) Imperfections in Flange Facing Finish for Raised Face Flanges	U-1
 Annex V (informative) Shipping Skid Examples	 V-1
Annex W (informative) Inspection Charts.....	W-1
Annex X (informative) Checklists	X-1
Annex Y (informative) Pump Temperature Equalization (PTE).....	Y-1
Annex Z (informative) Contract Documents and Engineering Design Data.....	Z-1
Bibliography	Bibliography-1
Figures	
1 Typical Gusset Design	22
2 Multipass Orifice Assembly	22
3 Shaft Axial Prevention Device Example.....	32
4 Set-up for Bearing Puller to Remove Bearings	35
5 Set-up for Hydraulic Press Removal of Bearings	36
6 Cavitation Damage	52
7 Example of Cavitation Damage to Impeller Vanes.....	53
8 Example of Cavitation Damage to Impeller Vanes.....	53
9 Example of Cavitation Damage.....	54
10 Example of Cavitation Damage to Vane.....	54
11 Example of Cavitation Eroding Blades	55
12 Example of Discharge Recirculation Damage.....	55
13 Example of Erosive Wear on an Impeller	56
14 Example of Abrasive Wear	56
15 Example of Abrasive Wear	56
16 Normal Wear Marks for Component—Acceptable to Reuse.....	58
17 Excessive Wear for Nonmetallic Component—Not Acceptable to Reuse.....	58
18 Fretting Under Thrust Collar	59
19 Locknut.....	61
20 Lock Washer	62
21 Diffuser Pump Cutwater	64
22 Eroded Volute Cutwater.....	64
23 Repaired Volute Cutwater.....	65
24 Abrasive Wear.....	65
25 Abrasive Wear.....	66
26 Abrasive Wear.....	66
27 Confined Controlled Compression Spiral Wound Gasket	67
28 Corrosion Damage	68
29 Diffuser Vane Leading Edge Erosion	72
30 Oil Ring Retainer	77
31 Proper Oiler Location.....	78
32 Coke Crusher for Single-stage Overhung-style Pump.....	87
33 Coke Crusher for Double-suction Between-Bearings-Style Pump	88

34	Typical Coke Crusher	88
35	Volute Cross Section Reduction.....	90
36	Volute Inserts.....	90
37	Methods of Increasing Volute Cross-sectional Area.....	91
38	Impeller Vane Overfiling	92
39	Impeller Vane Underfiling	92
40	Curve Shape Change for Underfiling	93
41	Showing Curve Shape Change for Increased Vanes.....	93
42	Showing Typical Vane Configurations.....	94
43	Suction Eye Area Differences	95
44	Showing a Curve Without Continuous Rise (Hooked Curve)	95
45	Cross Section of a Pump with Inducer.....	96
46	Inducer.....	96
47	Gap A Illustration.....	98
48	Gap A and Gap B.....	99
49	Impeller with Center Rib, Vanes Not Staggered.....	99
50	Impeller with Center Rib and Staggered Vanes	100
51	Impeller Center Rib Cross Section	100
52	Angle-trimmed Double-suction Impeller	100
53	Angle-trimmed Single-suction Impeller	101
54	Eye Reduction Ring or Stall Ring (to Reduce Suction Eye Recirculation for Low-flow Application) ...	101
55	Illustration of a Crowned Case.....	104
56	Gusset from API 610	106
57	Bearing Housing with Semicircular Mounting	108
58	Bearing Housing with 360°	108
59	Oil Sump.....	109
60	Bearing Housing Fan	110
61	Bearing Housing Fan Typical for OH Pumps	110
62	Bearing Housing Fan Typical for BB Pumps.....	110
63	Typical Heat Sink.....	111
64	Typical Heat Sink Mounting Location	111
65	OH Pump Cross Section with Heat Sink	112
66	Radial Load vs Flow	115
67	Erosive Wear Near Case Studs.....	119
68	Tack Welds for Case and Impeller Rings.....	127
69	Setscrew Location.....	129
70	Axial Pin Example.....	129
71	Setscrew Example.....	130
72	Radial Setscrew Holes	130
73	Key and Slot Wear Ring Anti-rotation Suction Ring Example.....	131
74	Key and Slot Wear Ring Anti-rotation Cover Ring Example.....	131
75	Typical Weld Areas for Diffuser	141
76	Location of Metal Gasket.....	142
77	Impeller Dimensions Relating to Balancing	155
78	Balance Correction Location	157
79	Multistage Rotor with Stationary Components Suspended	160
80	Diffuser-style Inner Bundle Assembly	161
81	Back-to-back Bearing Arrangement.....	173
82	Face-to-face Bearing Arrangement	173
83	Back-to-back and Tandem Bearing Arrangement.....	173
84	Spacer and Bearing Parallelism.....	174
85	Assembly Lift Measurement for OH1, OH2, and OH3 Pumps.....	176
86	Axial End Float Measurement for OH1, OH2, and OH3 Pumps	177
87	How to Cut a Parting Flange Gasket	187
88	Pressure Dam Bearing.....	189
89	Wedge Tri-land Bearing	190

90	Contact Verification	192
91	Example of a Lift Measurement for BB Pumps	194
92	Example of a Lift Measurement for Inner Bundle Assembly of BB Pumps.....	194
93	Example of an Axial End Float Measurement for BB Pumps	195
94	Example of End Float Measurement of the Inner Bundle Assembly	195
95	Example of Outer Casing for BB5 Pump with Discharge on End	202
96	Example of Outer Casing for BB5 Pump with Discharge in Center	203
97	Example of Volute-style Inner Bundle Assembly.....	203
98	Example of Diffuser-style Inner Bundle Assembly	203
A.1	Pump Type OH1.....	A-1
A.2	Pump Type OH2.....	A-1
A.3	Pump Type OH2 Typical Cutaway	A-2
A.4	Pump Type OH2 Typical Overview	A-2
A.5	Pump Type OH3.....	A-3
A.6	Pump Type OH3 Typical Cutaway	A-3
A.7	Pump Type OH3 Typical Overview	A-4
A.8	Pump Type OH4.....	A-4
A.9	Pump Type OH4 Typical Cutaway	A-5
A.10	Pump Type OH4 Typical Overview	A-5
A.11	Pump Type OH5.....	A-6
A.12	Pump Type OH5 Typical Cutaway	A-6
A.13	Pump Type OH5 Typical Overview	A-7
A.14a	Foot Mounted, Pump Type BB1	A-7
A.14b	Near Centerline Mounted, Pump Type BB1	A-8
A.15a	Foot Mounted, Pump Type BB1 Typical Cutaway.....	A-8
A.15b	Near Centerline Mounted, Pump Type BB1 Typical Cutaway.....	A-9
A.16a	Foot Mounted, Pump Type BB1 Typical Overview	A-9
A.16b	Near Centerline Mounted, Pump Type BB1 Typical Overview	A-10
A.17	Pump Type BB2.....	A-10
A.18	Pump Type BB2 Typical Cutaway.....	A-11
A.19	Pump Type BB2 Typical Overview	A-11
A.20	Pump Type BB3.....	A-11
A.21	Pump Type BB3 Typical Cutaway.....	A-12
A.22	Pump Type BB3 Typical Overview	A-12
A.23	Pump Type BB4.....	A-12
A.24	Pump Type BB4 Typical Cutaway.....	A-13
A.25	Pump Type BB4 Typical Overview	A-13
A.26	Pump Type BB5.....	A-14
A.27a	Bolted End Cover, Diffuser Style, Full Cartridge-Inner Casing, Pump Type BB5 Typical Cutaway	A-14
A.27b	Shear Ring End Cover, Diffuser Style, Full Cartridge-Inner Casing, Pump Type BB5 Typical Cutaway	A-15
A.27c	Bolted End Cover, Volute Style, Full Cartridge-Inner Casing, Pump Type BB5 Typical Cutaway	A-15
A.28	Bolted End Cover, Full Cartridge-Inner Casing, Pump Type BB5 Typical Overview	A-15
B.1	Flowchart of Pump Review of Problem and Repair	B-1
D-1	Steps in Liquid Penetrant Inspection	D-2
D.2	Principles of Magnetic Particle Inspection	D-5
D.3	Using Shaft Prods for Magnetic Particle Inspections.....	D-5
D.4	Using Coil on Shaft for Magnetic Particle Inspections.....	D-6
D.5	Using Coil on Impeller for Magnetic Particle Inspections.....	D-6
E.1	Typical Horizontal Dial Test Indicator	E-1
E.2	Proper Positioning of Contact Stylus.....	E-3
E.3	Inclination Error.....	E-3
E.4	Roundness Measurement.....	E-4
F.1	Bearing Arrangements.....	F-1

F.2	Oil Bath Heater.....	F-4
F.3	Induction Heater	F-5
F.4	Spanner Wrench Tightening Method.....	F-6
F.5	Lock nut Socket Tightening Method	F-7
F.6	Sleeve Used to Position Bearing onto Shaft	F-7
G.1	Running Traces and Applied Load	G-2
G.2	Raceway Flaking.....	G-3
G.3	Raceway Flaking.....	G-3
G.4	Raceway Flaking.....	G-4
G.5	Raceway Flaking.....	G-4
G.6	Raceway Flaking.....	G-5
G.7	Ball Surface Flaking	G-5
G.8	Raceway Flaking.....	G-6
G.9	Raceway Flaking.....	G-6
G.10	Raceway Flaking.....	G-7
G.11	Roller Flaking.....	G-7
G.12	Raceway Peeling	G-8
G.13	Raceway Peeling Enlargement G-8	
G.14	Roller Peeling.....	G-9
G.15	Raceway Peeling	G-9
G.16	Inner Ring Scoring	G-10
G.17	Roller Scoring	G-11
G.18	Inner Ring Scoring	G-11
G.19	Roller End Face Scoring.....	G-12
G.20	Inner Ring Scoring	G-12
G.21	Roller End Face Scoring.....	G-13
G.22	Cage Scoring	G-13
G.23	Inner Ring Smearing	G-14
G.24	Outer Ring Smearing	G-15
G.25	Raceway Smearing.....	G-15
G.26	Raceway Smearing.....	G-16
G.27	Raceway Smearing.....	G-16
G.28	Raceway Smearing.....	G-17
G.29	Roller Smearing	G-17
G.30	Inner Ring Chipping	18
G.31	Inner Ring Fracture	G-19
G.32	Inner Ring Fracture	G-19
G.33	Outer Ring Fracture.....	G-20
G.34	Outer Ring Cracking.....	G-21
G.35	Roller Cracking	G-21
G.36	Outer Ring Cracking.....	G-22
G.37	Outer Ring Cracking.....	G-22
G.38	Raceway Cracking.....	G-23
G.39	Inner Ring Cracking	G-23
G.40	Inner Ring Cracking	G-24
G.41	Roller Cracking	G-24
G.42	Cage Fracture	G-25
G.43	Cage Fracture	G-26
G.44	Cage Fracture	G-26
G.45	Cage Fracture	G-27
G.46	Cage Deformation.....	G-27
G.47	Cage Deformation.....	G-28
G.48	Cage Deformation.....	G-28
G.49	Cage Stepped Wear.....	G-29
G.50	Raceway Frosting.....	G-30
G.51	Outer Ring Dents	G-30

G.52	Inner Ring Dents.....	G-31
G.53	Roller Dents	G-31
G.54	Outer Ring Pits	G-32
G.55	Ball Pits	G-33
G.56	Inner Ring Wear	G-34
G.57	Outer Ring Wear	G-34
G.58	Inner Ring Fretting	G-35
G.59	Roller Wear.....	G-35
G.60	Inner Ring Fretting	G-36
G.61	Inner Ring Fretting	G-37
G.62	Outer Ring Fretting.....	G-37
G.63	Inner Ring False Brinelling	G-38
G.64	Outer Ring False Brinelling.....	G-39
G.65	Outer Ring False Brinelling.....	G-39
G.66	Roller False Brinelling	G-40
G.67	Inner Ring Creep.....	G-41
G.68	Outer Ring Creep.....	G-41
G.69	Inner Ring Seizure	G-42
G.70	Roller Seizure.....	G-43
G.71	Inner Ring Seizure	G-43
G.72	Outer Ring Seizure	G-44
G.73	Cage Seizure.....	G-44
G.74	Inner Ring Electrical Corrosion	G-45
G.75	Roller Electrical Corrosion	G-45
G.76	Inner Ring Electrical Corrosion	G-46
G.77	Ball Electrical Corrosion.....	G-46
G.78	Outer Ring Rust.....	G-47
G.79	Outer Ring Rust	G-48
G.80	Inner Ring Rust.....	G-48
G.81	Roller Rust	G-49
G.82	Inner Ring Mounting Flaws	G-50
G.83	Outer Ring Mounting Flaws.....	G-50
G.84	Roller Mounting Flaws	G-51
G.85	Inner Ring Discoloration.....	G-51
G.86	Inner Ring Discoloration.....	G-52
H.1	Preload Variations	H-7
I.1	Thrust Shoe Surface Abrasion.....	I-1
I.2	Concentric Scoring of Thrust Pad	I-2
I.3	Scoring of Pad	I-2
I.4	Tin Oxide Damage	I-3
I.5	Tin Oxide Damage	I-3
I.6	Thermal Ratcheting	I-4
I.7	Overheating, Oil Additives Plated Out	I-5
I.8	Overheating and Fatigue at Joint	I-5
I.9	Cracking of Pad due to Operation at Excessively High Temperatures	I-6
I.10	Cracking and Displacement of Pad due to Overheating Under Steady Conditions.....	I-6
I.11	Thermal Ratcheting due to Thermal Cycling Through Excessive Temperature Range in Service ..	I-7
I.12	Stray Shaft Currents/Electrical Pitting (Frosting)	I-8
I.13	Fine Hemispherical Pitting and Scoring of Bearing	I-9
I.14	Stray Shaft Currents/Electrical Pitting (Frosting) Journal Bearing.....	I-10
I.15	Edge Load Pivoted Shoe Showing Babbitt Mechanical Fatigue	I-11
I.16	Edge Load Journal Shell with Babbitt Mechanical Fatigue	I-12
I.17	Babbitt Fatigue in a Thin Thrust Plate.....	I-13
I.18	Babbitt Fatigue Cracking	I-14
I.19	Babbitt Fatigue Cracking	I-15
I.20	Thrust Shoe Cavitation Damage in Babbitt Face	I-16

I.21	Thrust Shoe Cavitation Toward Outside Diameter	I-17
I.22	Cavitation Damage on OD of Collar.....	I-18
I.23	Modification of Groove to Limit or Reduce Cavitation Damage	I-19
I.24	Bearing Wiped due to a Barreled Journal.....	I-20
I.25	Uneven Wear of Bearing due to Misalignment.....	I-21
I.26	Bearing with Formation of “Black Scab”	I-22
I.27	13 % Cr Journal Running in Bearing Shown in Figure I.24 Showing Severe “Machining” Damage.....	I-23
I.28	“Black Scab”—Wire Wooling—Formation on Thrust Pad	I-24
K.1	Single-suction Impeller Straight Cut Vanes (Vanes and Shrouds Same Diameter)	K-1
K.2	Single-suction Impeller Straight Cut Vanes (Vanes and Shrouds Different Diameters).....	K-1
K.3	Single-suction Impeller Angle (Oblique) Cut Vanes (Vanes and Shrouds Different Diameters)	K-2
K.4	Double-suction Impeller Straight Cut Vanes (Vanes and Shrouds Same Diameters).....	K-2
K.5	Double-suction Impeller Angle (Oblique) Cut Vanes (Vanes and Shrouds Different Diameters) ...	K-3
K.6	Mixed Flow Impeller	K-3
K.7	Vane Tip Width.....	K-4
K.8	Shroud to Blade Fillet Dressing	K-4
L.1	Thermal Spray Processes	L-4
N.1	Nonmetallic Component Thermal Growth Allowance	N-2
N.2	Typical Nonmetallic Wear Ring installed in a Metallic Holder	N-3
N.3	Holder Heating	N-4
N.4	Example of Chamfers.....	N-4
N.5	Example of Chamfers and Leading Edge	N-5
N.6	Example of Face Screw	N-6
N.7	Example of Radial Pin Installation.....	N-6
N.8	Example of Radial Pin Installation.....	N-7
O.1	Dynamic Radial Seal Grooves.....	O-2
O.2	Static Seal Groove.....	O-2
O.3	O-ring Dimensions	O-4
O.4	Compression Set.....	O-6
O.5	Extrusion	O-7
O.6	Nibbling	O-7
O.7	Installation Damage.....	O-8
O.8	Spiral Damage.....	O-9
O.9	Heat Damage.....	O-10
O.10	Chemical Degradation	O-12
O.11	Polymerization	O-14
O.12	Rapid Gas Decompression Damage.....	O-16
O.13	Rapid Gas Decompression.....	O-16
O.14	Nucleation Site and Fatigue Lines.....	O-17
O.15	Groove Overfill.....	O-18
P.1	OH1, OH2, OH3, OH4, and OH5 OH-style Pumps—Balance Flowchart	P-1
P.2	BB1, BB2, BB3, and BB5 Volute-style Pumps with Interference or Clearance Fit Impeller(s)—Balance Flowchart	P-2
P.3	BB1, BB2, BB3, BB4, and BB5 Diffuser-style Pumps with Interference Fit Impeller(s)—Balance Flowchart	P-3
P.4	BB1, BB2, BB3, BB4, and BB5 Diffuser-style Pumps with Clearance Fit Impeller(s)—Balance Flowchart	P-4
Q.1	Residual Unbalance Worksheet	Q-4
Q.2	Sample Residual Unbalance Worksheet for Left Plane (Metric)	Q-5
Q.3	Sample Residual Unbalance Worksheet for Right Plane (USC).....	Q-6
R.1	Piping Plan 01 Seal Chamber Details.....	R-7
R.2	Piping Plan 02 Seal Chamber Details.....	R-7
R.3	Piping Plan 03 Seal Chamber Details.....	R-8
R.4	Piping Plan 11 Seal Chamber Details.....	R-9
R.5	Piping Plan 12 Seal Chamber Details.....	R-9
R.6	Piping Plan 13 Seal Chamber Details.....	R-10

R.7	Piping Plan 14 Seal Chamber Details.....	R-10
R.8	Piping Plan 21 Seal Chamber Details.....	R-11
R.9	Piping Plan 22 Seal Chamber Details.....	R-12
R.10	Piping Plan 23 Seal Chamber Details.....	R-12
R.11	Piping Plan 31 Seal Chamber Details.....	R-13
R.12	Piping Plan 32 Seal Chamber Details.....	R-13
R.13	Piping Plan 41 Seal Chamber Details.....	R-14
R.14	Piping Plan 51 Seal Chamber Details.....	R-15
R.15	Piping Plan 52 Seal Chamber Details.....	R-16
R.16	Piping Plan 53A and 53B Seal Chamber Details.....	R-18
R.17	Piping Plan 53C Seal Chamber Details.....	R-19
R.18	Piping Plan 54 Seal Chamber Details.....	R-20
R.19	Piping Plan 55 Seal Chamber Details.....	R-22
R.20	Piping Plans 61 and 62 Seal Chamber Details	R-22
R.21	Piping Plan 65A Seal Chamber Details	R-23
R.22	Piping Plan 65B Seal Chamber Details	R-24
R.23	Piping Plan 66A Seal Chamber Details	R-24
R.24	Piping Plan 66B Seal Chamber Details	R-25
R.25	Piping Plan 71 Seal Chamber Details.....	R-26
R.26	Piping Plan 72 Seal Chamber Details.....	R-28
R.27	Piping Plan 74 Seal Chamber Details.....	R-29
R.28	Piping Plan 75 Seal Chamber Detail.....	R-31
R.29	Piping Plan 76 Seal Chamber Details.....	R-32
S.1	General Bolting Sequences for Circular and Non-circular Patterns	S-2
S.2	Typical Bolting Sequence for Axial Split Pump.....	S-2
T.1	Fully Crowned Stepped Key for Fly Cut Keyway.....	T-2
T.2	Keyway Filled with Half Key for Balancing	T-3
T.3a	Proper Key Installation.....	T-4
T.3b	Improper Key Installation.....	T-4
T.4	Top of Key to Shaft Dimension.....	T-5
T.5	Keyway Bore Dimension	T-5
T.6	Cross Section of Coupling Hub and Shaft Assembly	T-6
T.7a	Proper Key Length.....	T-6
T.7b1	Improper Key Length.....	T-6
T.7b2	Improper Key Length.....	T-7
T.8a	Acceptable Key for Fly-cut Keyway	T-7
T.8b1	Improper Key Length.....	T-7
T.8b2	Improper Key Length.....	T-8
T.9	Key Sitting in Keyway.....	T-9
T.10a	Proper Key to Keyway Corner Radius	T-9
T.10b	Improper Key to Keyway Corner Radius	T-9

Tables

1	General Components.....	41
2	General Components Repaired.....	41
3	Indication Acceptance Criteria.....	48
4	Maximum Gauss Levels	48
5	Materials Inspection Standards for Pressure Casings	49
6	Hydraulic Performance Testing Matrix	122
7	Number of Wear Ring Tack Welds.....	128
8	Number of Wear Ring Screw or Pins.....	128
9	Number of Radial Screws for Ring Retention	131
10	Number of Pad Welds.....	140
11	Hydrostatic Testing.....	149
D.1	Equivalent Hardness	D-10

G.1	Flaking Information.....	G-2
G.2	Peeling Information.....	G-8
G.3	Scoring Information.....	G-10
G.4	Smearing Information.....	G-14
G.5	Fracture Information.....	G-18
G.6	Cracks Information	G-20
G.7	Cage Damage Information	G-25
G.8	Denting Information.....	G-29
G.9	Pitting Information	G-32
G.10	Wear Information.....	G-33
G.11	Fretting Information.....	G-36
G.12	False Brinelling Information	G-38
G.13	Creep Information	G-40
G.14	Seizure Information.....	G-42
G.15	Electrical Corrosion Information	G-44
G.16	Rust and Corrosion Information	G-47
G.17	Mounting Flaws Information.....	G-49
G.18	Discoloration Information	G-51
G.19	Diagnostic Chart	G-53
H.1	Preload Variations.....	H-9
H.2	Stack Height Check	H-10
J.1	Material Combinations—Galling Resistance	J-1
L.1	Coatings and Overlays—Typical Uses	I-7
L.2	Thermal Spray Coating Recommended Minimum/Maximum Thickness Chart	I-8
O.1	O-ring Squeeze	O-3
Q.1	Trial Weight Multiplier vs Maximum Continuous Speed (Nmc).....	Q-2
R.1	Dual Seal Pressure Assembly Leak Test Sequence Summary	R-6
R.2	Piping Plan 01 Connections for Pressure Assembly Leak Test.....	R-7
R.3	Piping Plan 02 Connections for Pressure Assembly Leak Test.....	R-8
R.4	Piping Plan 03 Connections for Pressure Assembly Leak Test.....	R-8
R.5	Piping Plan 11 Connections for Pressure Assembly Leak Test.....	R-9
R.6	Piping Plan 12 Connections for Pressure Assembly Leak Test.....	R-9
R.7	Piping Plan 13 Connections for Pressure Assembly Leak Test.....	R-10
R.8	Piping Plan 14 Connections for Pressure Assembly Leak Test.....	R-11
R.9	Piping Plan 21 Connections for Pressure Assembly Leak Test.....	R-11
R.10	Piping Plan 22 Connections for Pressure Assembly Leak Test.....	R-12
R.11	Piping Plan 23 Connections for Pressure Assembly Leak Test.....	R-12
R.12	Piping Plan 31 Connections for Pressure Assembly Leak Test.....	R-13
R.13	Piping Plan 32 Connections for Pressure Assembly Leak Test.....	R-14
R.14	Piping Plan 41 Connections for Pressure Assembly Leak Test.....	R-14
R.15	Piping Plan 51 Connections for Pressure Assembly Leak Test (Outer Seal Is Open to Atmosphere and Is Not Being Tested)	R-15
R.16	Piping Plan 52 Connections for Pressure Assembly Leak Test (Outer Seal Is Open to Atmosphere and Is Not Being Tested)	R-16
R.17	Piping Plan 52 Connections for Outer Seal Pressure Assembly Leak Test (Pump and Inner Seal Still Pressurized)	R-17
R.18	Piping Plan 53A and 53B Connections for Inner and Outer Seal Pressure Assembly Leak Test	R-18
R.19	Piping Plan 53A and 53B Connections for Pressure Assembly Leak Test	R-18
R.20	Piping Plan 53C Connections for Inner and Outer Seal Pressure Assembly Leak Test.....	R-19
R.21	Piping Plan 53C Connections for Pressure Assembly Leak Test	R-19
R.22	Piping Plan 54 Connections for Inner and Outer Seal Pressure Assembly Leak Test	R-20
R.23	Piping Plan 54 Connections for Pressure Assembly Leak Test.....	R-21
R.24	Piping Plan 55 Connections Pressure Assembly Leak Test (Outer Seal Is Open to Atmosphere and Is Not Being Tested)	R-22
R.25	Piping Plan 55 Connections for the Outer Seal Pressure Assembly Leak Test	

	(Pump and Inner Seal Still Pressurized)	R-22
R.26	Piping Plans 61 and 62 Connections for Pressure Assembly Leak Test (Outer Seal Is Open to Atmosphere and Is Not Being Tested)	R-23
R.27	Piping Plan 65A Connections for Pressure Assembly Leak Test (Outer Seal Is Open to Atmosphere and Is Not Being Tested)	R-23
R.28	Piping Plan 65B Connections for Pressure Assembly Leak (Outer Seal Is Open to Atmosphere and Is Not Being Tested)	R-24
R.29	Piping Plan 66A Connections for Pressure Assembly Leak Test (Outer Seal Is Not Being Tested)	R-25
R.30	Piping Plan 66B Connections for Pressure Assembly Leak Test (Outer Seal Is Open to Atmosphere and Is Not Being Tested)	R-25
R.31	Piping Plan 71 Connections for the Pressure Assembly Leak Test (Outer Seal Is Open to Atmosphere and Is Not Being Tested)	R-27
R.32	Piping Plan 71 Connections for Outer Seal Pressure Assembly Leak Test (Pump and Inner Seal Still Pressurized)	R-27
R.33	Piping Plan 72 Connections for Pressure Assembly Leak Test (Outer Seal Is Open to Atmosphere and Is Not Being Tested)	R-28
R.34	Piping Plan 72 Connections for Outer Seal Pressure Assembly Leak Test (Pump and Inner Seal Still Pressurized)	R-28
R.35	Piping Plan 74 Connections for Inner and Outer Seal Pressure Assembly Leak Test	R-30
R.36	Piping Plan 74 Connections for Pressure Assembly Leak Test (Pump and Inner Seal Still Pressurized)	R-30
R.37	Piping Plan 75 Connections for Pressure Assembly Leak Test (Outer Seal Is Open to Atmosphere and Is Not Being Tested)	R-31
R.38	Plan 75 Connections for Outer Seal Pressure Assembly Leak Test (Pump and Inner Seal Are Not Pressurized)	R-31
R.39	Piping Plan 76 Connections for Pressure Assembly Leak Test (Outer Seal Is Open to Atmosphere and Is Not Being Tested)	R-32
R.40	Piping Plan 76 Connections for Outer Seal Pressure Assembly Leak Test (Pump and Inner Seal Are Not Pressurized)	R-33
S.1	Coarse-thread Series, UNC and UNRC	S-5
S.2	4-Thread Series, 4-UN and 4-UNR.....	S-6
S.3	6-Thread Series, 6-UN and 6-UNR.....	S-7
S.4	8-Thread Series, 8-UN and 8-UNR.....	S-8
S.5	12-Thread Series, 12-UN and 12-UNR	S-9
S.6	16-Thread Series, 16-UN and 16-UNR	S-10
S.7	20-Thread Series, 20-UN and 20-UNR	S-11
S.8	28-Thread Series, 28-UN and 28-UNR	S-12
S.9	32-Thread Series, 32-UN and 32-UNR	S-13
S.10	Cap Screw Head Markings.....	S-14
T.1	Suggested Keyway Fillet Radius and Key Chamfer.....	T-8
T.2	Key Size vs Shaft Diameter.....	T-10
U.1	Maximum Flange Face Imperfections	U-1
W.1	Fits.....	W-4
W.2	Runouts	W-5
W.3	Information.....	W-6
W.4	Surface Finish Pressure Boundary Surfaces.....	W-7
W.5	Surface Finish Flanges.....	W-8
W.6	Surface Finish Coupling Hubs	W-8
W.7	Surface Finish, Mounting Surfaces and Shims	W-9
W.8	Surface Finish Shaft Areas	W-9
W.9	Surface Finish Components.....	W-10
W.10	Surface Finish Instrumentation Mounting Surfaces	W-10
W.11	Surface Finish Balancing Mandrels Surfaces.....	W-10
W.12	Surface Finish Mating Surfaces	W-11
W.13	Contact Percentage for Split Line Surfaces	W-11
W.14	Spiral Wound Gasket Compression	W-11

W.15	Seal and Seal Chamber Fits	W-15
W.16	Seal and Seal Chamber Runouts	W-16
W.17	Oil and Flinger Ring Fits	W-19
W.18	Oil and Flinger Ring Information.....	W-20
W.19	OH1 and OH2 Part Number Descriptions	W-23
W.20	Stationary Component Fits.....	W-32
W.21	OH1 and OH2 Runouts	W-35
W.22	OH1 and OH2 Information.....	W-36
W.23	OH1 and OH2 Shaft Information	W-36
W.24	OH1 and OH2 Shaft Runouts (Phase-referenced)	W-37
W.25	OH1 and OH2 Shaft to Component Fits	W-38
W.26	OH1 and OH2 Impeller Information	W-39
W.27	OH1 and OH2 Impeller Runouts.....	W-40
W.28	OH1 and OH2 Component Bore Taper (for Straight Fit Bores)	W-40
W.29	OH3 Part Number Descriptions.....	W-43
W.30	OH3 Stationary Component Fits	W-53
W.31	OH3 Runouts	W-55
W.32	OH3 Information	W-56
W.33	OH3 Shaft Information.....	W-56
W.34	OH3 Shaft Runouts (Phase-referenced)	W-57
W.35	OH3 Shaft to Component Fits	W-57
W.36	OH3 Impeller Information.....	W-58
W.37	OH3 Impeller Runouts	W-59
W.38	OH3 Component Bore Taper (for Straight Fit Bores).....	W-60
W.39	Part Number Descriptions	W-62
W.40	OH4 Stationary Component Fits	W-70
W.41	OH4 Runouts	W-71
W.42	OH4 Pump Shaft to Component Fits	W-72
W.43	OH4 Impeller Information.....	W-73
W.44	OH4 Impeller Runouts	W-74
W.45	OH4 Component Bore Taper (for Straight Fit Bores).....	W-74
W.46	OH5 Part Number Descriptions.....	W-78
W.47	OH5 Stationary Component Fits	W-84
W.48	OH5 Runouts	W-85
W.49	OH5 Motor Shaft to Component Fits	W-86
W.50	OH5 Impeller Information.....	W-86
W.51	BB Shaft Runouts	W-88
W.52	BB Rotor Runouts.....	W-89
W.53	BB Impeller to Diffuser Positioning	W-89
W.54	NDE—Rolling Element Thrust Radial Bearing Design Part Number Descriptions.....	W-91
W.55	NDE—Rolling Element Thrust/Hydrodynamic Radial Bearing Design Part Number Descriptions...	W-92
W.56	NDE—Tilt Pad Thrust/Hydrodynamic Radial Bearing Design Part Number Descriptions	W-93
W.57	DE—Rolling Element Radial Bearing Design Part Number Descriptions.....	W-94
W.58	DE—Hydrodynamic Radial Bearing Design Part Number Descriptions	W-95
W.59	BB Bearing Housing Fits	W-100
W.60	BB Bearing Housing Runouts	W-103
W.61	BB Bearing Housing Shaft Information	W-104
W.62	BB Impeller Fits.....	W-108
W.63	BB Interference Fit Impellers Fit to Shell.....	W-109
W.64	BB Clearance Fit Impellers Fit to Shaft.....	W-109
W.65	BB Impeller Runouts	W-110
W.66	BB Impeller Information.....	W-110
W.67	BB1 Part Number Descriptions.....	W-113
W.68	BB1 Fits	W-114
W.69	BB1 Information	W-115
W.70	Single-stage, Single-cover Part Number Descriptions	W-118

W.71	Two Stage Part Number Descriptions.....	W-120
W.72	BB2 Fits	W-125
W.73	BB2 Information	W-126
W.74	BB2 Runouts.....	W-127
W.75	Additional Information for Two-stage Pumps.....	W-128
W.76	BB3 Part Number Descriptions.....	W-132
W.77	BB3 Fits	W-134
W.78	BB3 Information	W-136
W.79	BB4 Part Number Descriptions.....	W-139
W.80	BB4 Fits	W-142
W.81	BB4 Runouts.....	W-143
W.82	Horizontally Split—Volute-style Inner Casing with Bolted End Covers Part Number Descriptions	W-146
W.83	BB5 Volute- or Diffuser-style Pump Fits.....	W-149
W.84	BB5 Volute-style Pump Fits.....	W-149
W.85	BB5 Diffuser-style Pump Fits	W-151
W.86	BB5 Information	W-152
W.87	Hydraulic Forces Push the Wear Ring Off the Parent Part	W-153
W.88	Hydraulic Forces Push the Wear Ring onto the Parent Part	W-154
W.89	Rolling Element Bearing to Bearing Housing Fit (USC) (Modified H7 is to Ensure Clearance Fit)	W-155
W.90	Rolling Element Bearing to Bearing Housing Fit (SI Units) (Modified H7 is to Ensure Clearance Fit)	W-157
W.91	Rolling Element Bearing Fit to Shaft	W-159
W.92	Shaft and Rotor Runout Recommendations (BB-style Pumps)	W-161
W.93	Spiral Wound Gasket Groove Dimensions.....	W-161
W.94	Hydrodynamic Thrust Bearing Clearance (End Play)	W-162
W.95	Hydrodynamic Thrust Bearing Collar Thickness	W-162
W.96	Seal Chamber to Seal Gland Fit (H7/f7).....	W-163
W.97	Internal Running Clearances	W-165
W.98	Fixed Throat Bushing Clearances	W-166
W.99	Floating Carbon Throttle Bushing Diametral Clearances	W-166
X.1	Inspection of Installed Pump and Removal from Baseplate Checklist	X-2
X.2	Field Inspection (After Pump Has Been Removed from Its Base)	X-4
X.3	Field Repair	X-6
X.4	Shipment of Equipment or Components to or from Repair Shop	X-7
X.5	Receipt of Pump and Components by Repair Shop	X-8
X.6	Disassembly and Cleaning of Pump (in Repair Shop)	X-9
X.7	Shop Inspection of Disassembled Pump, Components, and Casing	X-10
X.8	Pump Modifications and Rerates.....	X-16
X.9	Repair Processes and New Component Manufacture Checklist	X-20
X.10	Rotor Assembly and Balancing	X-23
X.11	Shop Assembly of Pump	X-25
X.12	Conformance to Work Scope	X-37
X.13	Shipment of Equipment or Components to or from Repair Shop	X-38
X.14	Documentation	X-39
X.15	Receipt of Repaired Pump by Owner	X-41
X.16	Reinstallation of Pump and Systems in Field	X-43
X.17	Field Installation Data Form.....	X-46
X.18	Electric Motor Solo/Rotation Check Data Form.....	X-50
X.19	Electric Motor Solo/Rotation Check Data Form Start-up	X-51
Y.1	Pump Temperature Equalization	Y-5

Introduction

This document can be used for pumps and pump systems to guide the user along a path from perception of a problem through the resolution of the problem. Sections are provided that identify the important aspects of each topic encountered during the resolution of a problem. Topics include:

- inspections performed in the field and repair shop;
- shipping the pump to and from a repair shop;
- modifications and re-rates;
- repair techniques;
- rotor balancing;
- reassembly;
- reinstallation and startup;
- documentation.

Annex B is a high-level flowchart of the pump problem resolution process. The nature of the problem will determine which portions of this document are applicable. The Field and Repair Shop Work Scopes should indicate applicable portions of this practice.

The basic assumption of this practice is that the entire pump (pressure casing, rotor assembly, bearings, and seals) is removed for repair, with the possible exception of BB5 pumps.

Users of this recommended practice should be aware that further or differing recommendations may be needed for individual applications. This recommended practice is not intended to inhibit a vendor from offering, or the purchaser from accepting, alternative equipment or engineering solutions for the individual application. This may be particularly appropriate where there is innovative or developing technology. Where an alternative is offered, the vendor should identify any variations from this recommended practice and provide details.

A bullet (•) at the beginning of a paragraph indicates that either a decision is required or further information should be provided by the owner. This information should be stated in the quotation request or in the order.

Pump Repair

1 Scope and General Recommendations and Information

1.1 Scope

This recommended practice (RP) covers the minimum recommendations for the inspection and repair of API 610 pumps types OH1 through OH5 and BB1 through BB5. Refer to Annex A for figures and description of pump types.

This document covers the entire process of field inspection, modifications, inspection, upgrades, repair and/or new component manufacturer, reassembly of the pump casing and rotor in the shop, and the reinstallation and start-up of the pump in the field.

Pumps in hydrofluoric acid service may require inspection and repair methods that are beyond the scope of this RP.

Each phase of inspection will determine a work scope. The work scope will become more definitive as the inspection process progresses.

1.2 General Recommendations

1.2.1 The basis of repair recommendations should be to produce a safe reliable pump while:

- returning dimensions required for spare parts interchangeability to the latest design fits and clearances,
- maintaining interchangeability with other units,
- using existing spare parts,
- eliminating errors in manufacturing future spare parts that could be caused by undocumented dimensional changes,
- maintaining its torque transmission capabilities.

NOTE The latest design fits and clearances can be different than originally designed by the original equipment manufacturer (OEM), because rerates and/or upgrades could have been incorporated into the machine design.

1.2.2 Use of previously manufactured components and their acceptance criteria should be mutually agreed upon by all parties involved and documented in the work scope.

1.2.3 The repair shop should assume order responsibility.

1.3 Alternative Procedures

The repair shop or vendor may offer alternative procedures and designs. Any exception to this RP should be clearly stated in the proposal.

1.4 Conflicting Requirements

In case of conflict between this RP and the inquiry, the inquiry should govern. At the time of the order, the order governs.