

Introduction to Hydraulics and Pneumatics



Principles of Hydraulics

The word "hydraulics" generally refers to power produced by moving liquids. Modern hydraulics is defined as the use of confined liquid to transmit power, multiply force, or produce motion.


Pascal: "Pressure applied on a confined fluid is transmitted in all directions with equal force on equal areas".






Multiplication of Force


 Since liquid transmit the same amount of pressure in all directions. The force transmitted to the output piston is multiplied by a factor equal to the area ratio of the output piston to the input piston







Components of Hydraulic/Pneumatic Systems





Components of Hydraulic/Pneumatic Systems

- 1. Fluid: oil for hydraulic systems, air for pneumatics.
- 2. Reservoir: storage tank.
- Hydraulic pump (compressor in pneumatics): converts the mechanical energy into hydraulic energy by forcing fluid from the reservoir into the system.
- 4. Fluid lines: transport the fluid to and from the pump through the hydraulic system.
- 5. Valves: control pressure, direction and flow rate of the hydraulic fluid.
- Actuator: converts hydraulic energy into mechanical energy to do work.



Applications



Oil & Gas Drilling Rigs



Fork Lifts

Machine Tools
Injection Molders
Presses



Combines/Harvesters



Midsize to Large Tractors



Dozers/Crawlers



Hauler Trucks




Excavators






Example: lifting a load






Example: lifting a load





Example: lifting a load






Control valves

Control valves: are valves used to control conditions such as flow, pressure, and direction of flow.


- Pressure control valves.
- Flow control valves.
- Directional control valves
 - Check Valves
 - Directional valves



Pressure Control Valves



A pressure control valve is used to reduce the amount of pressure in a tank or system of pipes.






Pressure Control Valves

PRESSURE CONTROL VALVES

Pressure relief valve		Sequence valve	
F-∳P Direct operated	Pilot operated _F = ♦P	r-∳B Direct operated	Pilot operated B
			× A V
Pressure reducing valve		Counterpressure valve	
B Direct operated Pilot operated B		r	8
		- X X Y	



Flow Control Valves



Used to control fluid flow





Flow Control Valves


FLOW CONTROL VALVES







Directional control valves

Check Valves










Directional control valves

Directional valves






Directional valves

DIRECTIONAL CONTROL VALVES

Check valve					
Standard	Calibrated	Piloted operated	Piloted with drainage		
\	\$	₽	<u> </u>		
	Direction	nal valves			
2 ways - 2 positions	3 ways - 2 positions	4 ways - 2 positions	4 ways - 3 positions		
1 ·			XEII		
Controls for directional valves					
Mechanical	Pushbutton	Lever	Pedal		
HE .	□	<u> </u>	<u> </u>		
Controls for directional valves					
Spring	Cam	Electric (solenoid)	Electro-hydraulic		
₩	≔ [4	ZZ		
Controls for directional valves					
Pneumatic	Hydraulic	Electric (proportional)	Electro-hydraulic (proportional)		
	I	★ [ķa [



Example: Directional valves






- In hydraulics the pressure port is designated P and the return port R or T (for tank). The two other ports are designated A and B.
- Boxes to identify normal and operating positions.
- Arrows to identify flow directions.
- In Pneumatics the pressure port is numbered (1) and the exhaust port (3). The other two are numbered (2) and (4).




Example: 4-ports 2-position directional control valve






Example: 4-ports 3-position directional control valve






Example: 4-ports 3-position directional control valve





Example: 5-ports 3-position directional control valve





CYLINDERS


Graphic symbol	Item	Description
	Single acting cylinder	Return stroke by external force
	Single-acting cylinder	Return stroke through a spring
	Double seting cylinder	Single rod
	Double-acting cylinder	Double rod
	Cylinder with fixed	Cushioning on one side
	stroke end cushioning	Cushioning on both sides
	Cylinder with adjustable	Cushioning on one side
	stroke end cushioning	Cushioning on both sides
	Tolongonia gylindar	Single-acting
	Telescopic cylinder	Double-acting



Pneumatic Circuits



Flow control valve (with check)







Shuttle valve

A shuttle valve has two air inlets ' P_1 ' and ' P_2 ' and one air outlet 'A'. When compressed air enters through ' P_1 ', the sphere will seal and block the other inlet ' P_2 '. Air can then flow from ' P_1 ' to 'A'. When the contrary happens, the sphere will block inlet ' P_1 ', allowing air to flow from ' P_2 ' to 'A' only.










Pneumatic circuits

- Pneumatic control systems can be designed in the form of pneumatic circuits. A pneumatic circuit is formed by various pneumatic components, such as cylinders, directional control valves, flow control valves, etc.
- Pneumatic circuits have the following functions:
 - To control the injection and release of compressed air in the cylinders.
 - 2. To use one valve to control another valve.
- Displayed as Pneumatic circuit diagram.




Example: Signal inversion



When valve in operation mode output is off




Example: Memory Function




When valve 1 is operated output is on until valve 2 is on then output is off.



Example: Delay function






ON-signal delay

OFF-signal Delay




Example: Delay function cont.



Time delay valve




Example: Speed control






Example: OR Function






Example: AND Function






Example: NOT Function







Example: Double acting cylinder






Example: Transport system








Example: Vehicle door operation system






Controlling the movement of the vehicle doors (OFF)

Controlling the movement of the vehicle doors (ON)




Example: Plastic forming



When the push button is pressed, the 5/2 valve changes state and the cylinder outstrokes. As it outstrokes, it pushes the former together and the hot plastic sheet is pressed into shape. As this happens it also actuates the roller. Air now flows through the restrictor and starts to fill up the reservoir. Once the reservoir is full, the 5/2 valve changes state and the cylinder instrokes, ready for the process to begin again.




Example: full automatic circuit



As the piston instrokes, it trips valve A and the 5/2 valve changes state and the piston is sent positive. When it is fully outstroked, it trips valve B and the 5/2 valve returns to its original position, allowing the piston to instroke. The process begins all over again and continues to operate.



Example: Sequential control (furnace for heat treatment)



The sequence of operations for this process is as follows.

- (a) An operator pushes a button to start the process.
- (b) The furnace door is opened.
- (c) The block is pushed into the furnace and the piston instrokes.
- (d) The furnace door is closed.
- (e) The sequence stops.

