

Desalination Project Cost Estimating and Management



Nikolay Voutchkov

Desalination Project Cost Estimating and Management



Taylor & Francis

Taylor & Francis Group

<http://taylorandfrancis.com>

Desalination Project Cost Estimating and Management

Authored by
Nikolay Voutchkov



CRC Press

Taylor & Francis Group

Boca Raton London New York

CRC Press is an imprint of the
Taylor & Francis Group, an **informa** business

CRC Press
Taylor & Francis Group
6000 Broken Sound Parkway NW, Suite 300
Boca Raton, FL 33487-2742

© 2019 by Taylor & Francis Group, LLC
CRC Press is an imprint of Taylor & Francis Group, an Informa business

No claim to original U.S. Government works

Printed on acid-free paper

International Standard Book Number-13: 978-0-8153-7414-5 (Hardback)

This book contains information obtained from authentic and highly regarded sources. Reasonable efforts have been made to publish reliable data and information, but the author and publisher cannot assume responsibility for the validity of all materials or the consequences of their use. The authors and publishers have attempted to trace the copyright holders of all material reproduced in this publication and apologize to copyright holders if permission to publish in this form has not been obtained. If any copyright material has not been acknowledged, please write and let us know so we may rectify in any future reprint.

Except as permitted under U.S. Copyright Law, no part of this book may be reprinted, reproduced, transmitted, or utilized in any form by any electronic, mechanical, or other means, now known or hereafter invented, including photocopying, microfilming, and recording, or in any information storage or retrieval system, without written permission from the publishers.

For permission to photocopy or use material electronically from this work, please access www.copyright.com (<http://www.copyright.com/>) or contact the Copyright Clearance Center, Inc. (CCC), 222 Rosewood Drive, Danvers, MA 01923, 978-750-8400. CCC is a not-for-profit organization that provides licenses and registration for a variety of users. For organizations that have been granted a photocopy license by the CCC, a separate system of payment has been arranged.

Trademark Notice: Product or corporate names may be trademarks or registered trademarks, and are used only for identification and explanation without intent to infringe.

Library of Congress Cataloging-in-Publication Data

Library of Congress Cataloging-in-Publication Data

Names: Voutchkov, Nikolay, author.

Title: Desalination project cost estimating and management / Nikolay Voutchkov.

Description: Boca Raton : Taylor & Francis, a CRC title, part of the Taylor & Francis imprint, a member of the Taylor & Francis Group, the academic division of T&F Informa, plc, 2018. | Includes bibliographical references.

Identifiers: LCCN 2018031237 | ISBN 9780815374145 (hardback : acid-free paper)

Subjects: LCSH: Saline water conversion--Costs. | Saline water conversion plants--Management.

Classification: LCC TD479.3 .V68 2018 | DDC 628.1/670681--dc23

LC record available at <https://lccn.loc.gov/2018031237>

Visit the Taylor & Francis Web site at
<http://www.taylorandfrancis.com>

and the CRC Press Web site at
<http://www.crcpress.com>

Contents

Preface.....	xiii
Acknowledgments.....	xvii
Author	xix
Units.....	xxi
Abbreviations	xxiii

Chapter 1	Project Cost Overview.....	1
1.1	Introductory Remarks.....	1
1.2	Project Cost Definitions.....	4
1.2.1	Capital Costs	5
1.2.2	Operation and Maintenance Costs	5
1.2.3	Cost of Water Production	6
1.2.3.1	Water Production Costs of BWRO Desalination Plants	6
1.2.3.2	Cost of Water Produced by SWRO Desalination Plants	8
	References	9

Chapter 2	Project Cost Factors.....	11
2.1	Introductory Remarks.....	11
2.2	Cost Factors within the Control of the Plant Owner	11
2.2.1	Project Size.....	11
2.2.2	Capacity Availability Factor.....	18
2.2.3	Source Water Quality	25
2.2.4	Target Product Water Quality	29
2.2.5	Concentrate Disposal Method.....	31
2.2.6	Power Supply and Unit Power Cost.....	31
2.2.7	Project Risk Profile	36
2.2.7.1	Permitting (Licensing) Risks.....	38
2.2.7.2	Entitlement Risks.....	38
2.2.7.3	Power Supply Risks	39
2.2.7.4	Construction Risks.....	39
2.2.7.5	Source Water Risks.....	40
2.2.7.6	Technology Risks.....	40
2.2.7.7	Regulatory Risks	42
2.2.7.8	Operational Risks	42
2.2.7.9	Desalinated Water Demand Risk.....	43
2.2.7.10	Financial Risks	43
2.2.8	Project Geographic Location	44
2.2.9	Other Project Cost Factors	45

2.3	Cost Factors Beyond the Control of Plant Owner	46
2.3.1	Environmental Regulations.....	47
2.3.1.1	Intake-Related Environmental Regulations and Their Potential Impacts on Costs.....	47
2.3.1.2	Discharge-Related Environmental Regulations and Their Potential Impacts on Costs.....	52
2.3.2	Contractor Market Experience and Perception	53
	References	54
Chapter 3	Cost Estimates – Types and Accuracy	57
3.1	Introductory Remarks.....	57
3.2	Conceptual Cost Estimate	57
3.3	Preliminary Cost Estimate	59
3.4	Budgetary Cost Estimate.....	60
3.5	Detailed Cost Estimate	61
3.6	Overview of Existing Cost Models	61
	References	63
Chapter 4	Capital Costs	65
4.1	Introductory Remarks.....	65
4.2	Construction Costs	67
4.2.1	Site Preparation, Roads, and Parking-Related Construction Costs	67
4.2.2	Intake Construction Costs.....	68
4.2.2.1	Construction Costs of Open Onshore Intakes.....	69
4.2.2.2	Construction Costs of Open Offshore Intakes.....	69
4.2.2.3	Construction Costs of Subsurface Intakes.....	72
4.2.2.4	Construction Costs of Intake Pump Stations	73
4.2.3	Pretreatment Construction Costs.....	73
4.2.3.1	Construction Costs of Band and Drum Screens.....	74
4.2.3.2	Construction Costs of Wedge Wire Screens.....	75
4.2.3.3	Construction Costs of Microscreens.....	75
4.2.3.4	Construction Costs of Lamella Settlers and DAF Clarifiers	77
4.2.3.5	Construction Costs of Granular Media Pretreatment Filters	77

- 4.2.3.6 Construction Costs of Membrane Pretreatment Filters 77
 - 4.2.3.7 Construction Costs of Cartridge Filter System..... 79
 - 4.2.4 RO System Equipment Costs 79
 - 4.2.4.1 Construction Costs for Single-Pass SWRO Systems..... 82
 - 4.2.4.2 Construction Costs for Full Two-Pass SWRO Systems..... 83
 - 4.2.4.3 Construction Costs for Split-Partial Two-Pass SWRO Systems 85
 - 4.2.5 Post-Treatment Construction Costs 86
 - 4.2.6 Concentrate Disposal System–Related Construction Costs 88
 - 4.2.7 Waste and Solids Handling–Related Construction Costs 90
 - 4.2.8 Construction Costs of Electrical and Instrumentation Systems 91
 - 4.2.9 Construction Costs of Auxiliary and Service Equipment and Utilities..... 91
 - 4.2.10 Building Construction Costs 91
 - 4.2.11 Startup, Commissioning, and Acceptance Testing Costs 92
 - 4.3 Costs of Project Engineering Services 92
 - 4.3.1 Preliminary Engineering Costs..... 92
 - 4.3.2 Pilot Testing Costs..... 92
 - 4.3.3 Detailed Design Costs..... 93
 - 4.3.4 Construction Management and Oversight Costs 93
 - 4.4 Project Development Costs..... 93
 - 4.4.1 Project Administration, Contracting, and Management 94
 - 4.4.2 Environmental Permitting..... 94
 - 4.4.3 Legal Services 94
 - 4.5 Project Financing Costs..... 95
 - 4.5.1 Government Financing..... 95
 - 4.5.2 Conventional (Bond or Construction Loan) Financing 95
 - 4.5.3 Private Project Financing 97
 - 4.5.4 Interest During Construction..... 101
 - 4.5.5 Debt Service Reserve 102
 - 4.5.6 Other Financing Costs..... 102
 - 4.6 Contingency..... 102
 - 4.7 Example of Desalination Project Capital Cost Estimate..... 102
 - 4.7.1 Project Description..... 103
 - 4.7.1.1 Plant Capacity and Availability 103
 - 4.7.1.2 Plant Location, Intake, and Discharge..... 103

- 4.7.1.3 Intake Water Quality 103
 - 4.7.1.4 Product Water Quality 104
 - 4.7.1.5 Key Plant Treatment Facilities..... 104
 - 4.7.1.6 Plant Operations 105
 - 4.7.2 Capital Cost Estimate..... 106
- References 109

Chapter 5 Operation and Maintenance Costs 111

- 5.1 Introductory Remarks..... 111
- 5.2 Power Costs 112
 - 5.2.1 Power Costs Associated with Desalination Plant
 Energy Use 112
 - 5.2.2 Power Costs Associated with Unit Price of
 Electricity 115
- 5.3 Chemicals 116
- 5.4 Labor..... 116
- 5.5 Maintenance and Repairs 117
- 5.6 Membrane and Cartridge Filter Replacement 118
- 5.7 Waste Stream Management 119
- 5.8 Environmental and Performance Monitoring 120
- 5.9 Indirect O&M Costs 121
- 5.10 Operation and Maintenance Cost Curves..... 121
 - 5.10.1 Intake Structures and Piping – Annual O&M Cost.... 121
 - 5.10.1.1 O&M Cost of Open Onshore Intakes 121
 - 5.10.1.2 O&M Cost of Open Offshore Intakes..... 121
 - 5.10.2 Intake Pump Stations – Annual O&M Cost..... 123
 - 5.10.3 Band and Drum Screens – Annual O&M Cost..... 124
 - 5.10.4 Wedgewire Screens – Annual O&M Cost 125
 - 5.10.5 Microscreens – Annual O&M Cost 125
 - 5.10.6 Cartridge Filter System – Annual O&M Cost 125
 - 5.10.7 Lamella Settlers and DAF Clarifiers – Annual
 O&M Cost 127
 - 5.10.8 Granular Media Pretreatment Filters – Annual
 O&M Cost 128
 - 5.10.9 Membrane Pretreatment Filters – Annual O&M
 Cost..... 129
 - 5.10.10 SWRO Desalination Systems – Annual O&M Cost.... 129
 - 5.10.10.1 Single-Pass SWRO Systems 130
 - 5.10.10.2 Full Two-Pass SWRO Systems..... 130
 - 5.10.10.3 Split-Partial Two-Pass SWRO Systems.... 131
 - 5.10.11 Post-Treatment Systems – Annual O&M Cost..... 132
 - 5.10.11.1 Post-Treatment – Stabilization..... 132
 - 5.10.11.2 Post-Treatment – Disinfection 133
 - 5.10.12 Other Direct Annual O&M Costs 133
 - 5.10.13 Indirect Annual O&M Costs..... 134

- 5.11 Example of Desalination Project O&M Cost Estimate..... 134
 - 5.11.1 Annual O&M Cost Estimate Based on “Rule-of-Thumb Range Method” 136
 - 5.11.2 Annual O&M Cost Estimate Using the “Cost-Curve Based Method” 137
- References 139

- Chapter 6** Water Production Cost 141
 - 6.1 Introductory Remarks..... 141
 - 6.2 Fixed Cost Components..... 141
 - 6.2.1 Capital Cost Recovery 141
 - 6.2.2 Other Fixed Costs..... 142
 - 6.3 Variable Cost Components 143
 - 6.4 Water Production Cost..... 144
 - 6.4.1 Impact of Desalination Plant Location on the Cost of Water 146
 - 6.4.2 Impact of Environmental Issues on the Cost of Water 146
 - 6.4.3 Impact of Labor Market on the Cost of Water 148
 - 6.4.4 Impact of Method of Project Delivery on the Cost of Water 150
 - 6.5 Example of Desalination Project Cost of Water Estimate..... 150
 - References 152

- Chapter 7** Project Implementation and Costs..... 153
 - 7.1 Project Delivery Alternatives and Costs 153
 - 7.1.1 Design-Bid-Build (DBB) 153
 - 7.1.1.1 Project Parties and Their Roles 153
 - 7.1.1.2 Construction Contractor Procurement Process 155
 - 7.1.1.3 Key Advantages and Disadvantages..... 155
 - 7.1.2 Construction Manager at Risk (CMR) 157
 - 7.1.2.1 Project Parties and Their Roles 157
 - 7.1.2.2 CMR Contractor Procurement Process 158
 - 7.1.2.3 Key Advantages and Disadvantages..... 158
 - 7.1.3 Design-Build (DB) 159
 - 7.1.3.1 Project Parties and Their Roles 159
 - 7.1.3.2 DB Contractor Procurement Process..... 160
 - 7.1.3.3 Design-Build – Key Advantages and Disadvantages 160
 - 7.1.4 Design-Build-Operate (DBO) 161
 - 7.1.4.1 Project Parties and Their Roles 161
 - 7.1.4.2 DBO Contractor Procurement Process 162
 - 7.1.4.3 Key Advantages and Disadvantages..... 163

7.1.5	Build-Own-Operate-Transfer (BOOT)	163
7.1.5.1	Project Parties and Their Roles	163
7.1.5.2	BOOT Contractor Procurement Process.....	165
7.1.5.3	Key Advantages and Disadvantages.....	165
7.2	Project Implementation Schedule and Phasing	167
7.2.1	Project Duration	167
7.2.2	Project Phasing.....	168
	References	168

Chapter 8 Cost Management..... 169

8.1	Introductory Remarks.....	169
8.2	Cost and Energy Use Factors and Their Management	169
8.3	Alternatives for Reducing Desalination Plant Energy Use and Costs	170
8.3.1	Collocation of Desalination and Power Plants	171
8.3.2	Use of Lower Salinity Source Water.....	174
8.3.3	Use of Higher Productivity/Lower Energy SWRO Elements.....	177
8.3.4	Use of Large-Diameter RO Membrane Elements	178
8.3.4.1	Commercial Products	178
8.3.4.2	Diameter, Length, Membrane Area, and Productivity.....	181
8.3.4.3	Membrane Materials and Performance	182
8.3.4.4	Seal Carrier	182
8.3.4.5	Element Interconnection	183
8.3.4.6	Brine Seal Location	183
8.3.4.7	Membrane Element Costs	183
8.3.4.8	Membrane Vessels	184
8.3.4.9	RO Train Number, Size, and Configuration	185
8.3.4.10	Large-Size Element Loading and Unloading	187
8.3.5	Hybrid Membrane Configuration	190
8.3.6	RO Systems for High-Recovery Plant Design.....	192
8.3.6.1	Multi-stage Dual Turbocharger (MSDT) High-Recovery SWRO System....	192
8.3.6.2	E-REX High-Recovery SWRO System.....	193
8.3.7	Split-Partial Two-Pass RO System with Front Permeate Treatment.....	195
8.3.8	Increased High-Pressure Pump Efficiency	196
8.3.9	Improved Energy Recovery.....	197
8.4	Recent and Future Desalination Technology Advances.....	198
8.4.1	Nanostructured Membranes	198
8.4.2	Forward Osmosis (FO).....	199
8.4.3	Membrane Distillation (MD)	200

8.4.4	Electrochemical Desalination	201
8.4.5	Capacitive Deionization (CDI).....	202
8.4.6	Biomimetic Membranes	202
8.5	Potential Impact of Future Technologies on Desalination Costs	203
8.6	Concluding Remarks	204
	References	205
Glossary		209
Index		215



Taylor & Francis

Taylor & Francis Group

<http://taylorandfrancis.com>

Preface

One of the key challenges associated with the wider implementation of seawater desalination is its relatively high cost. This book provides engineering guidelines for assessment of seawater desalination project construction, operation and maintenance (O&M) costs, and presents practical approaches for cost management using state-of-the-art technologies and equipment.

The book describes step-by-step desalination cost-estimating procedures and practices. It clearly explains key factors impacting desalination costs and available tools to manage such impacts. It also provides an overview of the main cost-saving features incorporated in some of the best-in-class seawater desalination plants worldwide and shares lessons learned from the implementation of recent low- and high-cost desalination projects. This book contains example construction, O&M and water production cost estimates for a typical desalination project.

At present, membrane reverse osmosis (RO) desalination is the fastest growing technology for the production of fresh water from saline water sources. Desalination plants use less energy to produce the same volume of fresh water than thermal desalination facilities. Therefore, this book focuses exclusively on the cost estimating of reverse osmosis desalination projects.

Preparation of cost estimates for the construction, funding, and operation of desalination plants is more complex and demanding than that for conventional water treatment facilities in terms of professional skills, knowledge, and understanding of treatment processes, technologies, and equipment employed in the desalination processes. As the advances in desalination technology make desalination more competitive to other alternative sources of water supply, preparation of accurate cost estimates for the construction and operation of desalination projects becomes of critical importance for identifying the size and role of desalination in the mix of alternatives that provide sustainable and reliable water supply portfolio for municipal coastal centers around the world.

This book provides detailed information on how to determine the costs associated with the implementation of seawater RO desalination plants. The book's content covers practically all aspects of cost estimating: from fundamentals, to factors impacting project costs; type and accuracy of cost estimates; overview of existing cost models and their practical use; and detailed guidance for calculation of capital costs, operation and maintenance (O&M) expenditures, and fresh water production costs of desalination projects. The book also has capital and O&M cost curves for key desalination facilities as well as examples for the preparation of cost estimates.

This book consists of eight chapters, which follow the process of determining all desalination project cost components of capital, O&M and water production costs. Each chapter includes essential knowledge, numerous practical tips, and rules-of-thumb for the preparation of budgetary cost estimates. Moreover, this book contains easy-to-use curves, which helps in preparing budgetary construction and O&M cost estimates as a function of the desalination project size and the type of applied technology and equipment – from open intakes to clarification and filtration pretreatment

systems; reverse osmosis facilities, membranes, and equipment; and post-treatment facilities.

Chapter 1 (Project Cost Overview) contains background information on desalination project cost-related definitions and fundamentals needed to understand the procedures and calculations of key desalination project costs, as well as to learn about the parameters used for cost comparison of desalination facilities and equipment.

Chapter 2 (Project Cost Factors) presents the key factors that have a significant impact on the capital, O&M and desalinated water production costs of desalination plants and provides indexes that quantify and compare the impact of these factors on the expenditures for seawater reverse osmosis (SWRO) desalination projects with different fresh water production capacity, source and product water qualities, design availability, method of funding and delivery, concentrate disposal alternatives, project risk profile, power supply source and tariff structure, and project risk profile. This chapter addresses both cost factors that are within the control of the project owner and can be adjusted to control costs, as well as factors that the owner cannot influence directly, but have to consider and reflect into the project cost estimates.

Chapter 3 (Cost Estimates – Type and Accuracy) describes what key project information is needed to prepare accurate conceptual, preliminary, budgetary, and detailed cost estimates of desalination projects. This chapter also discusses the accuracy of the various types of cost estimates and the purposes for which such estimates are used when planning and implementing desalination projects. Chapter 3 also contains an overview of existing cost models widely used by desalination project planners and practitioners worldwide.

Chapter 4 (Capital Costs) provides an overview of key components of capital expenditures typically incorporated in desalination project cost estimates. The capital costs are divided into two main groups of expenditures – direct (construction) costs and indirect (soft) costs. The construction cost components addressed in this chapter are: plant site-related costs; intake and pretreatment costs; RO system expenditures; post-treatment costs; concentrate disposal and waste and solids handling costs; expenditures related to the installation of the electrical and instrumentation system; building costs; and plant startup, commissioning, and acceptance testing costs. The chapter also has guidance for the calculation of all indirect capital costs, including: costs of project engineering services; project development costs, expenditures associated with project funding and contingency provisions. Chapter 4 also contains cost curves for all main plant facility and equipment components such as: intake structures and piping and pump station; band, drum, and wedgewire screens; microscreens (strainers); cartridge filtration systems; lamella settlers and dissolved air flotation (DAF) clarifiers; granular media and membrane pretreatment filters; single and two-pass SWRO systems; and lime and calcite post-treatment systems. This chapter also illustrates the use of the cost curves for the preparation of a budgetary construction cost estimate for a 100,000 m³/day SWRO desalination plant.

Chapter 5 (Operation and Maintenance Costs) defines the key components of plant O&M costs and presents practical information of how to estimate such costs. This chapter incorporates detailed information on cost estimating and control of the following main direct O&M cost components: power; chemicals; labor; maintenance and repairs; membrane and cartridge filter replacement; desalination plant

waste stream management; and environmental and performance monitoring of plant operations. The chapter also features estimating of indirect O&M costs, such as staff training, plant administration, laboratory services, contingencies, and insurance. Chapter 5 also contains annual O&M cost curves for the same equipment and facilities for which construction costs are provided in Chapter 4. In addition, this chapter illustrates an estimate of the annual O&M costs for a 100,000 m³/day SWRO desalination plant.

Chapter 6 (Water Production Cost) presents methodology for determining the cost of production of desalinated water from seawater applying SWRO membrane separation. The chapter discusses the calculation of the fixed and variable components of the water production cost and explains how this cost varies with plant capacity and availability factor. The chapter contains an example for the calculation of the cost of water produced by a 100,000 m³/day SWRO desalination plant.

Chapter 7 (Project Implementation and Costs) is dedicated to cost impacts of the commonly used methods for project delivery such as design-bid-build (DBB); design-build-operate (DBO); and build-own-operate-transfer (BOOT). The chapter emphasizes the key contractual structure provisions, advantages and disadvantages of the alternative project delivery methods in terms of construction costs, annual O&M expenditures, and water production costs and provides lessons learned from the implementation of seawater desalination projects worldwide. The chapter gives practical guidance of what project delivery and implementation features have been incorporated in recent SWRO desalination projects that have yielded the lowest costs of water production as well as what key project implementation factors have resulted in high costs in plant construction and operation. Chapter 7 also discusses the impact of the project delivery schedule on the plant construction costs and elaborates on the typical causes for project delays and construction cost overruns.

Chapter 8 (Cost Management) presents an overview of the latest design approaches, technologies and desalination process configurations widely used in practice for management of the construction, and O&M and water production costs for seawater reverse osmosis desalination projects. This chapter discusses cost and energy use factors and trends, and describes specific technologies, equipment, and membranes which have proven to be effective tools for desalination project cost management such as: collocation of desalination and power plants; use of lower salinity source water; higher productivity RO membrane elements; large-diameter membranes; hybrid and split-permeate RO membrane configurations; and the use of pumps and energy recovery devices of high energy efficiency. In addition, the chapter contains information on future desalination technology advances and research directions, which have the potential to yield significant further reduction of the costs for producing fresh water from saline water resources.

This book is intended for desalination project planners, engineers, and designers; water utility professionals involved in the development of water resource management plans; equipment and membrane developers; operation and troubleshooting specialists; as well as for students and teachers in the desalination field. The book contains need-to-know desalination project cost-estimating practices and information, which would benefit practitioners, decision-makers, and scholars alike.



Taylor & Francis

Taylor & Francis Group

<http://taylorandfrancis.com>

Acknowledgments

I would like to express my appreciation to the fellow professionals, colleagues, and associates who have reviewed various portions of this book and have provided constructive comments and suggestions. Special note of gratitude to the many operators, desalination plant managers, equipment and membrane manufacturers, and public utilities in the United States, Australia, Japan, Bahrain, United Arab Emirates, Spain, Cyprus, Kingdom of Saudi Arabia, and other parts of the world who have contributed valuable cost and technology-related information used in this book.

Special appreciation is extended to Eng. Meshal Alawad for his support work on collection and analysis of cost information from desalination plants worldwide and on the development of the cost curves included in the book.

I gratefully appreciate the assistance of Ms. Emma Kaiser for her artistic contribution toward the preparation of the figures and graphs included in the book.

Finally, my deep and sincere gratitude to Dr. Boris Liberman, Chief Technology Officer of IDE, for his inspiration, encouragement, and impetus to write this book.



Taylor & Francis

Taylor & Francis Group

<http://taylorandfrancis.com>

Author

Mr. Voutchkov is a registered professional engineer and a board certified environmental engineer (BCEE) by the American Academy of Environmental Engineers. He has over 25 years of experience in planning, environmental review, permitting and implementation of large seawater desalination, water treatment, and water reclamation projects in the United States and abroad.

Mr. Voutchkov has extensive expertise with all phases of seawater desalination project delivery: from conceptual scoping, pilot testing, and feasibility analysis; to front end and detailed project design; environmental review and permitting; contractor procurement; project construction and operations oversight/asset management.

Mr. Voutchkov is President of Water Globe Consultants, LLC – a private company specialized in providing expert advisory services in the field of seawater desalination and reuse. For over 11 years prior to establishing his project advisory firm, Mr. Voutchkov was a Chief Technology Officer and Corporate Technical Director for Poseidon Resources, a private company involved in the development of the largest seawater desalination projects in the United States.

In recognition of his outstanding efforts and contribution to the field of seawater desalination, Mr. Voutchkov has received a number of prestigious awards from the International Desalination Association, the International Water Association, the WaterReuse Association and the American Academy of Environmental Engineers.

He is one of the principal authors of the American Water Works Association's Manual of Water Supply Practices on Reverse Osmosis and Nanofiltration and of the World Health Organization's Guidance for the Health and Environmental Aspects Applicable to Desalination. Mr. Voutchkov has authored over 10 books and 40 technical articles in the field of water and wastewater treatment and reuse.



Taylor & Francis

Taylor & Francis Group

<http://taylorandfrancis.com>

Units

Bar – unit for pressure, 1 bar = 14.5 psi

cm – centimeter

°C – degrees Celsius – unit of temperature

d – day

GW – gigawatt – 1 GW = 1 million kW

ha – hectare

hr – hour

Hp – horsepower (unit of power)

kg – kilogram

km – kilometer

kW – kilowatt (unit of power)

kWh – kilowatt-hour (unit of energy)

kWh/m³ – kilowatt hours per cubic meter (measure of energy used to produce or convey one cubic meter of fresh (desalinated) water)

l or L – liter

Lmh – liter per square meter per hour

m – meter

m² – square meter

m³ – cubic meter

mm – millimeter

mg/L – milligrams per liter

m³/day – cubic meters per day

MW – megawatt – unit for power – 1 MW = 1,000 kW

μ – μm or micrometer (one-millionth of a meter)

μg/L – microgram per liter

μS/cm – micro-Siemens per centimeter – unit of specific conductivity of water

psu – practical salinity units (1 psu = 1,000 mg/L)

ppb – parts per billion (1 ppb = 1 μg/L)

ppm – parts per million (1 ppm = 1 mg/L)

ppt – parts per thousand (1 ppt = 1,000 mg/L)

psi – Unit of pressure – pounds per square inch

s – second

yr – year

Abbreviations

AfDB	African Development Bank
ADC	Affordable Desalination Collaboration
ASTM	American Society of Testing and Materials
AWWA	American Water Works Association
BOOT	Build-own-operate-transfer
BTA	Best Technology Available
BWRO	Brackish water reverse osmosis
Ca	Calcium
CCI	Construction cost index
CDI	Capacitive deionization
CEB	Chemically enhanced backwash
CEDI	Continuous Deionization
CDI	Capacitive Deionization
CIF	Climate Investment Funds
CIP	Clean-in-place
CO₂	Carbon dioxide
CPI	Consumer Price Index
CMR	Construction Manager at Risk
CNT	Carbon nanotubes
CRF	Capital recovery factor
CWA	Clean Water Act
DBB	Design-bid-build
DBO	Design-build-operate
DEEP	Desalination Economic Evaluation Program
DO	Dissolved oxygen
EBRD	European Bank for Reconstruction and Development
ED	Electrodialysis
EDR	Electrodialysis Reversal
ENR	Engineering News Record
EP	Equator Principles
EPC	Engineering, Procurement and Construction
EPFI	Equator Principle Financial Institutions
ERT	Energy Recovery Technology
FO	Forward Osmosis
GHG	Greenhouse Gas
GMP	Guaranteed Price Maximum
GRP	Glass Reinforced Plastic
GWI	Global Water Intelligence
H₂SO₄	Sulfuric Acid
HDD	Horizontal Directionally Drilled
HDPE	High-Density Polyethylene
IAEA	International Atomic Energy Agency

IRENA	International Renewable Energy Agency
IRR	Internal Return on Investment
ISD	Internally Staged Design
IWPP	Independent Water and Power Project
IX	Ion Exchange
FRP	Fiberglass Reinforced Plastic
KSA	Kingdom of Saudi Arabia
LIBOR	London Inter-Bank Offered Rate
LSI	Langlier Saturation Index
MD	Membrane Distillation
MED	Multi-effect Distillation
MED-TVC	Multi-effect Distillation with Thermal Vapor Compression
MENA	Middle East and North Africa
MF	Microfiltration
MSDT	Multistage Dual Turbocharger
MSF	Multistage Flash Distillation
Mg	Magnesium
MGD	Million Gallons per Day
MLD	Mega Liters per Day: 1 MLD = 1,000 m ³ /day
MM	Million
MTBE	Methyl Tertiary Butyl Ether (gasoline additive)
Na	Sodium
NaOH	Sodium Hydroxide
NGO	Non-Government Organization
NDMA	N-nitrosodimethylamine
NST	Nanostructured
NTU	Nephelometric Turbidity Unit
NUS	National University of Singapore
OEM	Original Membrane Manufacturer
O&M	Operation and Maintenance
ORP	Oxidation-Reduction Potential of Water
PAC	Powdered Activated Carbon
PP	Polypropylene
PPA	Power Purchase Agreement
PPP	Public-Private Partnership
PV	Photovoltaic
PVC	Polyvinyl Chloride
RFQ	Request for Qualifications
RO	Reverse Osmosis
SAR	Sodium Absorption Ratio
SDI	Silt Density Index
SOQ	Statement of Qualifications
SP	Salt Passage
SPC	Special Project Company
SWCC	Saline Water Conversion Corporation of Saudi Arabia
SWIM-SM	Sustainable Water Integrated Management – Support Mechanism

SWRCB	State Water Resource Control Board – California
TAK	Toray Advanced Materials Korea
TDS	Total Dissolved Solids
TFN	Thin-Film Nano-composite
TN	Total Nitrogen
TP	Total Phosphorus
TSS	Total Suspended Solids
UF	Ultrafiltration
UAE	United Arab Emirates
US, USA	United States of America
USBR	US Bureau of Reclamation
USEPA	United States of America's Environmental Protection Agency
VC	Vacuum Compression
WaTER	Water Treatment Estimation Routine
WDR	Water Desalination Report
WHO	World Health Organization
WPA	Water Purchase Agreement
WRA	Water Reuse Associates
WRRF	Water Reuse Research Foundation
WTP	Water Treatment Plant
WWTP	Wastewater Treatment Plant
Y	Plant Recovery, %



Taylor & Francis

Taylor & Francis Group

<http://taylorandfrancis.com>

1 Project Cost Overview

1.1 INTRODUCTORY REMARKS

Desalination is gaining popularity as an alternative water supply resource as many municipalities and utilities worldwide are facing increasing population growth pressures, shortage of suitable local water resources, and more stringent water quality regulations. Until recently, use of seawater desalination was limited to desert-climate dominated regions. Recent technological advances and associated decreases in water production costs and energy demand have expanded use of desalination in coastal areas traditionally supplied with fresh water resources (Bazargan, 2018; Gude, 2018).

At present, more than 19,000 desalination plants worldwide produce a total of 99.8 million cubic meters per day (m^3/day) of fresh water from seawater and brackish water (GWI, 2017) and provide approximately 1% of the world's drinking water supply. The number and size of desalination projects worldwide have been growing at a rate of 5%–6% per year since 2010, which corresponds to an addition of 3.0–4.0 million m^3/day of newly installed desalination plant fresh water production capacity every year.

This growth is due to a number of long-term global trends including: (1) steadily increasing population growth and associated demand for fresh drinking water in urbanized coastal areas; (2) prolonged drought in the arid and semi-arid coastal areas of the world; and (3) limited availability of untapped traditional low-cost fresh water resources in these areas. Arid and semi-arid coastal zones of the world are inhabited by over 70% of the world's population and are usually the fastest growing and most urbanized areas.

In total, 18% of the existing desalination plants are large size (i.e., have fresh water production capacity of over 100,000 m^3/day) and 36% are medium size (i.e., have a production capacity of 10,000–100,000 m^3/day). Medium and large size plants contribute approximately 90% (86 million m^3/day) of the existing total installed desalination plant capacity worldwide.

A clear recent trend in seawater desalination is the construction of larger capacity plants, which deliver an increasingly greater portion of the fresh water supply of coastal cities around the globe. While most of the large desalination plants built between 2000 and 2010 were typically designed to supply only 5%–10% of the drinking water of large coastal urban centers, today most regional or national desalination project programs in countries such as Spain, Australia, Israel, Algeria, and Singapore aim to secure 25%–30% of their long-term drinking water needs with desalinated seawater.

In the next 5 years, the largest investments in new desalination projects are projected to occur in the Middle East and North Africa (US\$28.2 billion), East Asia and the Pacific (US\$9.6 billion), North America (US\$5.1 billion), Latin America/Caribbean (US\$4.9 billion), and Western Europe (US\$2.9 billion) (GWI, 2017).

Since 2010, reverse osmosis (RO) desalination has been the main technology of choice for production of fresh water from saline water worldwide (Figure 1.1).

The prevalence of this desalination technology is due to the fact that for most saline sources and applications worldwide, it yields fresh water at overall energy use and costs lower than those of thermal desalination technologies such as multi-effect distillation (MED) and multi-stage flash distillation (MSF) – see Table 1.1.

At present, over 50% of the existing desalination plants are located in the Middle East and North Africa (MENA) region. The majority of the plants built in this region over the past 5 years employ seawater RO (SWRO) membrane desalination (Figure 1.2) for production of fresh water. The steady trend of increasing use of SWRO membrane desalination in the MENA region is mainly attributed to the lower energy use, high efficiency, and lower fresh water production costs associated




FIGURE 1.1 Breakdown of installed desalination plants worldwide by technology (2017).

TABLE 1.1
Energy and Water Production Costs for Alternative Desalination Technologies

Process/Energy Type	MED	MSF	VC	BWRO	SWRO
Steam pressure (ata)	0.2–0.4	2.5–3.5	Not needed	Not needed	Not needed
Electric energy equivalent (kWh/m³)	4.5–6.0	9.5–11.0	NA	NA	NA
Electricity consumption (kWh/m³)	1.2–1.8	3.2–4.0	8.0–12.0	0.3–2.8	2.5–4.0
Total energy use (kWh/m³)	5.7–7.8	12.7–15.0	8.0–12.0	0.3–2.8	2.5–4.0
Water production costs (US\$/m³)	0.7–3.5	0.9–4.0	1.0–3.5	0.2–1.8	0.5–3.0

Note: NA – Not applicable.




FIGURE 1.2 Breakdown of installed desalination plants in MENA by technology (2017).

with this technology as compared to thermal desalination (Ghaffour et al., 2013; Loutatidou et al., 2014).

The decline of thermal desalination is reflected in the recent decision of Saudi Arabia’s government not to build any MSF plants in the future, after the construction of the largest hybrid (MSF and SWRO) desalination plant in the world in Ras Al-Khair (WDR, 2017). This facility incorporates a 727,000 m³/day MSF plant and 310,000 m³/day SWRO plant. A similar trend toward preferential use of SWRO desalination technology for future projects is observed in other Middle Eastern countries such as Oman, Qatar, and the United Arab Emirates as well as in most countries in North Africa (Caldera and Breyer, 2017; Shazhad et al., 2017).

Source water salinity is one of the most important factors determining desalination project design and costs (AWWA, 2007; Papapetrou et al., 2017). Based on the salinity of the source water they process, desalination plants can be divided into three broad categories: low-salinity and high-salinity brackish water desalination plants, and seawater desalination plants.

Low-salinity brackish water (BW) desalination plants often have a relatively simple single-stage RO system configuration and are typically designed to treat water of total dissolved solids (TDS) concentration between 500 and 2,500 mg/L. For such plants, it is common that 5%–30% of the source water flow is bypassed and blended with permeate produced by the RO system. Therefore, such facilities are relatively less costly to build and operate.

Depending on the target water quality and method of concentrate disposal, low-salinity BWRO plants may employ more than one RO stage in order to reduce concentrate volume and costs. For example, the majority of the BWRO plants in Florida and Texas are low-salinity groundwater desalination plants. It should be pointed out that the low-salinity surface water BWRO plants usually produce desalinated water at 10%–20% higher cost, usually because of the more costly and complex pretreatment.

High-salinity BWRO plants are configured to process brackish source waters with TDS content in a range of 2,500–10,000 mg/L, usually treat the entire source

water flow, and as a minimum incorporate a two-stage RO system. Typically, fresh water production costs of high-salinity desalination plants are 15%–35% higher than those of low-salinity desalination projects. The main cost differences originate from the higher energy use associated with the elevated source water salinity, the more complex RO system configuration, and the lower fresh water recovery at which such plants typically operate.

Seawater desalination projects are designed to process source water of salinity between 15,000 and 46,000 mg/L. Usually such plants are configured as multi-pass, multi-stage RO systems, which operate at significantly lower recoveries and have higher energy use than brackish water desalination plants. In addition, SWRO membrane elements and vessels are more costly because they are designed to withstand higher pressures. As a result, the costs for desalinating seawater are usually measurably higher than those for producing the same quality of fresh water by brackish water desalination.

Depending on the target product water quality and site-specific conditions such as energy costs and concentration of other source water constituents besides sodium and chloride, saline waters of TDS concentration between 10,000 and 15,000 mg/L could be processed by both seawater and brackish water desalination systems.

While brackish water desalination plants are less costly to build and operate, often brackish water sources are not readily available and usually are fairly limited in volume and extraction rate. Seawater reverse osmosis desalination is the most widely used membrane salt separation technology at present, because it allows tapping into the largest natural source of water on the planet – the seawater contained in the oceans and seas.

Approximately 75% (1.6 million m³/day) of the new globally installed desalination plant capacity for the period of June 2016 to July 2017 (2.14 million m³/day) was for seawater desalination and only 15% (0.32 million m³/day) was for brackish water desalination (GWI, 2017). The remaining 10% (0.32 million m³/day) of the desalination plants have applied other water treatment technologies such as electrodialysis reversal (EDR), ion exchange (IX), forward osmosis (FO), and capacitive deionization (CDI).

This trend is expected to continue in the future with an overall slowdown of the construction of new brackish water desalination plants, because most of the known brackish water aquifers near large urbanized centers worldwide are already tapped in, and brackish water in general is of limited availability. Only 1.1% of the worldwide water resources are located in brackish water aquifers while 97.5% of the planet's water is in the oceans and seas. Therefore, this book focuses mainly on cost estimating of seawater reverse osmosis desalination projects.

1.2 PROJECT COST DEFINITIONS

The key economic parameters of seawater reverse osmosis desalination projects are:

- Capital costs;
- Operation and maintenance costs;
- Cost of water production.

1.2.1 CAPITAL COSTS

Capital costs include all expenditures associated with desalination project implementation: from the time of conceptual development, through design, permitting, financing, construction, commissioning, and acceptance testing for continuous operation. Construction costs encompass all direct expenditures needed to build plant source water intake and concentrate discharge systems and all project-related structures; procure and install all facility equipment; install and connect plant piping and service utilities; and deliver desalinated water to final user(s). Because of their direct association with the construction of physical facilities, construction costs are also referred to as “direct” or “hard” capital costs. Construction costs of seawater desalination plants are typically 50%–85% of the total capital costs.

The remaining 15%–50% of capital costs are often referred to as “indirect” or “soft” costs. These costs are associated with all engineering, administrative, permitting, and funding efforts necessary to bring the project to fruition. In addition, indirect capital costs incorporate expenditures needed to procure contractors for design, construction, and operation of the desalination project.

Total project capital costs are typically presented in monetary units (e.g., US\$) and are estimated either for the year when project construction is initiated or are referenced to the middle of the construction period. Depending on the type, length, and term of project funding, capital costs are often converted to monetary units per year and referred to as amortized or annualized costs (US\$/yr). In addition, both capital and construction costs are sometimes presented as expenditures per unit of desalination project fresh water production capacity (e.g., US\$/m³/day or US\$/1,000 gallons).

1.2.2 OPERATION AND MAINTENANCE COSTS

Operation and maintenance costs are all expenditures associated with desalination plant operations (power, chemicals, labor, and replacement of consumables, such as membranes and cartridge filters); with maintenance of plant equipment, buildings, grounds and utilities; and with compliance with all plant operation and environmental permits, and other pertinent regulatory requirements. The operation and maintenance costs associated with a given project are typically expressed as the all-inclusive operational expenditures for a period of one year (e.g., US\$/yr) or as operational costs for the production of unit volume of desalinated water (e.g., US\$/m³).

Operation and maintenance (O&M) costs may be divided into two main categories: fixed and variable. Fixed O&M costs are annual expenditures that are not a function of the actual amount of fresh water produced by the desalination plant. Such O&M expenditures include labor costs (staff wages and fringe benefits), costs for routine preventive equipment maintenance, environmental and performance monitoring, operational insurance, administrative costs, and other miscellaneous overhead expenses.

Variable O&M costs are typically proportional to the actual volume of desalinated water produced by the desalination plant and include expenditures for power; chemicals; replacement of RO membranes, pretreatment membranes (if membrane pretreatment is used), and cartridge filters; as well as expenditures for disposal of

waste (screenings, spent membrane cleaning chemicals, spent backwash water, disposal of dewatered residuals if pretreatment backwash is treated before, and pumping costs for conveyance and disposal of plant concentrate and other liquid discharges). Typically variable costs are 50%–85% of the total annual O&M costs of SWRO desalination plants, while the fixed costs are 15%–50% of these expenditures.

1.2.3 COST OF WATER PRODUCTION

Cost of water is an economic parameter that incorporates all project capital and annual O&M expenditures associated with water production. Typically this cost parameter is expressed in monetary units per unit volume of desalinated water (e.g., US\$/m³). The total cost of fresh water production (cost of water) is calculated by dividing the sum of the amortized (annualized) capital costs (e.g., US\$/yr) and the annual O&M costs (e.g., US\$/yr) by the total actual or projected annual volume of fresh water produced by the desalination plant, expressed in m³/yr. For a typical SWRO plant, the amortized capital costs and the O&M costs are usually in a range of 40%–60% of the total cost of water, each.

1.2.3.1 Water Production Costs of BWRO Desalination Plants

Table 1.2 provides a summary of the costs of fresh water production of low-salinity and high-salinity brackish water desalination plants. The cost summary presented in this table is based on comparative analysis of over 40 brackish water desalination plants worldwide. The actual costs of the individual projects used to generate Table 1.2 were adjusted for time scale, scope, and location to provide a common base for comparison.

Review of Table 1.2 indicates that at present (i.e., year 2018) the industry-wide average cost for production of fresh water by low-salinity and high-salinity BWRO plants is US\$0.7/m³ and US\$0.9/m³, respectively. As anticipated, use of low-salinity brackish water yields lower fresh water production costs. However, it is interesting to note that the cost difference is not proportional to salinity.

Often, low-salinity sources may contain additional contaminants such as silica, cyanide, iron, manganese, or large quantities of organics and dissolved gases that have a profound impact on plant construction costs because their removal usually

TABLE 1.2
Water Production Costs of Medium and Large Size BWRO Desalination Plants

Classification	Cost of Water (US\$/m ³)	
	Low-Salinity BWRO Plants	High-Salinity BWRO Plants
Low-end bracket	0.2–0.4	0.3–0.6
Medium range	0.5–0.8	0.7–1.0
High-end bracket	1.0–1.5	1.3–1.8
Average	0.7	0.9

requires additional treatment steps and expenditures. In addition, typically both low-salinity and high-salinity brackish water plants use the same type of RO membrane elements, vessels, and pumps, which have the same unit costs per processed capacity (i.e., their costs are mainly determined by plant production flow and recovery, and are not as significantly impacted by source water salinity as they are by production flow).

Figures 1.3 and 1.4 show a breakdown of the water production costs of low-salinity and high-salinity BWRO plants by main components: direct (construction) and indirect capital costs; and power and other O&M costs. For low-salinity desalination plants, construction costs (i.e., direct capital costs) are typically the largest component of the water production costs. The wide range of these costs is mainly attributed to the economy of scale, and differences in intake and concentrate disposal cost components.




FIGURE 1.3 Typical cost of water breakdown for low-salinity BWRO plants.




FIGURE 1.4 Typical cost of water breakdown for high-salinity BWRO plants.

Comparative analysis of Figures 1.3 and 1.4 indicates that in high-salinity BWRO plants power expenditures are a slightly larger portion of the total water production costs (typically because of the higher source water salinity). However, the energy cost component is not directly proportional to the salinity because high-salinity BWRO plants often apply energy recovery devices, which typically are not cost attractive for low-salinity BWRO plants, and also operate at lower recoveries, which results in elevated construction costs and lower energy use.

1.2.3.2 Cost of Water Produced by SWRO Desalination Plants

Table 1.3 presents the range of water production costs of medium and large size seawater reverse osmosis desalination projects. Information for this table is compiled based on comparative review of over 50 desalination projects in the United States, Australia, Europe, the Middle East, the Caribbean, and other parts of the world. As seen in Table 1.3, at present (in 2018 US\$) the average industry-wide cost of production of desalinated water by reverse osmosis is approximately US\$1.1/m³.

Comparison of Tables 1.2 and 1.3 reveals that on average seawater desalination production costs are 1.2–1.6 times higher than those for producing fresh water by high-salinity and low-salinity brackish water desalination, respectively. When comparing some individual projects however, this difference could be significantly higher.

For example, the cost of water production of a low-salinity BWRO project in the low-end cost bracket (i.e., US\$0.2–0.4 m³/day) could be over 10 times higher than the water production cost of a SWRO desalination project in the high-end cost bracket (US\$1.6–3.0/m³). While factually accurate, such comparisons are misleading if they are taken out of context of the site-specific project conditions, which may differ very significantly from one project to another.

Figure 1.5 depicts a typical breakdown of the fresh water production costs of medium and large size seawater reverse osmosis desalination projects. Although the ratio between the key cost components varies from project to project, the largest pieces of the “cost pie” are usually the plant construction expenditures (i.e., the direct capital costs), power, and the other O&M costs (i.e., maintenance, chemicals, membranes, etc.). The indirect capital costs, which mainly include expenditures for project engineering, development, and finance, are also a measurable portion (typically 10%–20%) of the water production costs.

TABLE 1.3
Water Production Costs of Medium and Large Size SWRO Desalination Plants

Classification	Cost of Water (US\$/m ³)
Low-end bracket	0.5–0.8
Medium range	0.9–1.5
High-end bracket	1.6–3.0
Average	1.1




FIGURE 1.5 Seawater reverse osmosis plant – cost of water breakdown.

Comparison of Figures 1.3 through 1.5 indicates that capital costs for BWRO facilities are usually a higher portion of the total water production expenditures than those for SWRO plants (45%–76% vs. 40%–60%). In BWRO projects, energy contributes 10%–30% of the total costs, as compared to SWRO projects where the energy contribution is usually in a range of 20%–35%, and in extreme conditions for remote plant locations with high unit energy costs, energy expenditures for SWRO desalination could exceed 50% of the total costs of water production.

REFERENCES

AWWA, 2007, *Reverse Osmosis and Nanofiltration, Manual of Water Supply Practices*, American Water Works Association (AWWA), Denver, CO.

Bazargan, A., Editor, 2018, *A Multidisciplinary Introduction to Desalination*, River Publishers, Denmark/Netherlands.

Caldera, U., Breyer, C., 2017, Learning curve for seawater reverse osmosis desalination plants: Capital cost trend of the past, *Present and Future, Water Resources Research*, 53, pp. 1–16.

Ghaffour, N., Missimer, M. T., Amy, L. G., 2013, Technical review and evaluation of the economics of water desalination: Current and future challenges for better water supply sustainability, *Desalination*, 309, pp. 197–207.

Gude, V. G., Editor, 2018, *Sustainable Desalination Handbook. Plant Selection, Design and Implementation*, Butterworth-Heinemann, An Imprint of Elsevier, Oxford, Cambridge.

GWl, 2017, *IDA Desalination Yearbook 2017-2018, Global Water Intelligence (GWl) and International Desalination Association (IDA)*, Media Analytics Ltd., Oxford, UK.

Loutatidou, S., Chalermthal, B., Marpu, P. R., Arafat, H., 2014, Capital cost estimation of RO plants: GGC countries versus Southern Europe, *Desalination*, 347, pp. 103–111.

Papapetrou, M., Cipollina, A., La Commare, U., Micale, G., Zargosa, G., Kosmadakis, G., 2017, Assessment of methodologies and data used to calculate desalination costs, *Desalination*, 419, pp. 8–19.

Shahzad, M. W., Burhan, M., Ang, L., Ng, K. C., 2017, Energy-water-environment nexus underpinning future desalination sustainability, *Desalination*, 413, pp. 52–64.

WDR, 2017, Saudi Arabia Desal market re-ignited, *Water Desalination Report (WDR)*, 53 (1), pp. 2–3.



Taylor & Francis

Taylor & Francis Group

<http://taylorandfrancis.com>

Project Cost Overview

AWWA , 2007, Reverse Osmosis and Nanofiltration, Manual of Water Supply Practices, American Water Works Association (AWWA), Denver, CO.

Bazargan, A. , Editor, 2018, A Multidisciplinary Introduction to Desalination, River Publishers, Denmark/Netherlands.

Caldera, U. , Breyer, C. , 2017, Learning curve for seawater reverse osmosis desalination plants: Capital cost trend of the past, Present and Future, Water Resources Research, 53, pp. 116.

Ghaffour, N. , Missimer, M. T. , Amy, L. G. , 2013, Technical review and evaluation of the economics of water desalination: Current and future challenges for better water supply sustainability, Desalination, 309, pp. 197207.

Gude, V. G. , Editor, 2018, Sustainable Desalination Handbook. Plant Selection, Design and Implementation, Butterworth-Heinemann, An Imprint of Elsevier, Oxford, Cambridge.

GWl , 2017, IDA Desalination Yearbook 2017-2018, Global Water Intelligence (GWl) and International Desalination Association (IDA), Media Analytics Ltd., Oxford, UK.

Loutatidou, S. , Chalermthal, B. , Marpu, P. R. , Arafat, H. , 2014, Capital cost estimation of RO plants: GGC countries versus Southern Europe, Desalination, 347, pp. 103111.

Papapetrou, M. , Cipollina, A. , La Commare, U. , Micale, G. , Zargosa, G. , Kosmadakis, G. , 2017, Assessment of methodologies and data used to calculate desalination costs, Desalination, 419, pp. 819.

Shahzad, M. W. , Burhan, M. , Ang, L. , Ng, K. C. , 2017, Energy-water-environment nexus underpinning future desalination sustainability, Desalination, 413, pp. 5264.

WDR , 2017, Saudi Arabia Desal market re-ignited, Water Desalination Report (WDR), 53 (1), pp. 23.

Project Cost Factors

Alspack, B. , Watson, I. , 2011, SWRO costs: Dont believe everything you read, IDA Journal, Second Quarter, 3 (2), pp. 2228.

Al-Karaghoul, A. , Rene, D. , Kazmerski, L.I. , 2009, Solar and wind opportunities for water desalination in the Arab region, Renewable and Sustainable Energy Reviews, 13, pp. 23972407.

Al-Karaghoul, A. , Kazmerski, L.I. , 2013, Energy consumption and water production cost of conventional and renewable-energy-powered desalination processes, Renewable Sustainable Energy Review, 24, pp. 343356.

55 AWWA , 2007, Voutchkov, N. , Bergman, R. facility design and construction, in Reverse Osmosis and Nanofiltration, Manual of Water Supply Practices M 46, Second Edition, American Water Works Association, Denver, CO.

Blanco, J. , Alarcon-Padilla, D.C. , Zaragoza, G. , Palenzuela, P. , Guillen, E. , Ibarra, M. , 2011, Solar energy and desalination processes: Status and development perspective, Water Desalination Conference in the Arab Countries (ARWADEX), April 1720, Riyadh, Saudi Arabia.

Caldera, U. , Breyer, C. , 2017, Learning curve for seawater Reverse Osmosis Desalination plants: Capital cost trend of the past, Present and Future, Water Resources Research, 53, pp. 116.

Cotruvo, J. , Voutchkov, N. , Fawell, J. , Payment, P. , Cunliffe, D. , Lattemann S. , 2010, Desalination technology, Health and Environmental Impacts, CRC Press and IWA Publishing, Boca Raton, MA, London, New York.

EP Association , 2013, Equator Principles III, Equator Principles (EP) Association, June.

Fiorenza, G. , Sharma, V.K. , Braccio, G. , 2003, Techno-economic evaluation of a solar powered water desalination plant, Energy Conservation Management, 44, pp. 22172240.

Ghaffour, N. Bundschuh, J. , Mahmoudi, H. , Goosen, M.F.A. , 2015, Renewable energy-driven desalination technologies: A comprehensive review on challenges and potential applications of integrated systems, Desalination, 356, pp. 94114.

Gude, V.G. , 2016, Desalination and sustainability an appraisal and current perspective, Desalination, 89, pp. 87106.

GWl , 2015, Desalination Markets 2016, Published by Media Analytics, Ltd., Oxford, UK.

IRENA , 2012, Water Desalination Using Renewable Technology, International Renewable Energy Agency, Technology Brief I12, March.

Karagiannis, I. , Soldatos, P. , 2008, Water desalination cost literature: Review and assessment, Desalination, 223, pp. 448456.

Lapiente, E. , 2012, Full cost of desalination. A case study of the Segura River Basin, *Desalination*, 300, pp. 4045.

Loutatidou, S. , Chalermthai, B. , Marpu, P.R. , Ararat, H.A. , 2014, Capital cost estimation of RO plants: GCC countries versus Southern Europe, *Desalination*, 347, pp. 103111.

Liberman, B. , 2002, The Importance of Energy Recovery Devices in Reverse Osmosis Desalination, *The future of Desalination in Texas Volume 2, Technical Papers, Case Studies Desalination Technology Resources (report # 363)*, Texas Water Development Board, USA, December.

Moch Jr., I. , 2002, A 21st century study of global seawater reverse osmosis operating and capital costs, *Proceedings of IDA World Congress*, Manama, Bahrain, March 813.

Moser, M. , Trieb, F. , Fichter, T. , Kern, J. , 2013, Renewable desalination: A methodology for cost comparison, *Desalination and Water Treatment*, 51, pp. 46.

Papapetrou, M. , Cipollina, A. , La Commare, U. , Micale, G. , Zaragoza, G. , Kosmadakis, G. , 2017, Assessment of methodologies and data used to calculate desalination costs, *Desalination*, 419, pp. 819.

Palenzuela, P. , Zaragoza, G. , Alarcon, D. , Blanco, J. , 2011, Simulation and evaluation of the coupling of coupling of desalination units to parabolic trough solar power plants in the Mediterranean region, *Desalination*, 281, pp. 379397.

Pinto, F.S. , Marques, R.C. , 2017, Desalination project economic feasibility: A standardization of cost determinants, *Renewable and Sustainable Energy Reviews*, 78, pp. 904915.

Quteishat, K. , Abu-Arabi, A. , 2012, Promotion of Solar Desalination in the MENA Region, Middle East Desalination Research Center, Muscat, Oman. (Available at: <http://shebacss.com/rd/docs/rdrsrs003.pdf>)

Shatat, M. , Worall, M. , Riffat, S. , 2013, Opportunities for solar water desalination worldwide: A review, *Sustainable Cities and Society*, 9, pp. 6780.

56 SWRCB , 2015, California Ocean Plan, 2015, State Water Resources Control Board, State of California, California Environmental Protection Agency, Sacramento, California.

Thomson, M. , 2003, Reverse Osmosis Desalination of Seawater Powered by Photovoltaics without Batteries, Thesis, UK: Loughborough University.

Voutchkov, N. , 2017, Pretreatment for Reverse Osmosis Desalination, Elsevier, New York, NY.

WHO , 2011, Guidelines for Drinking Water Quality, Fourth Edition, World Health Organization (WHO), Geneva, Switzerland.

Wittholz, M.K. , ONeil, B.K. , Colby, C.B. , Lewis, D. , 2008, Estimating the cost of desalination plants using a cost database, *Desalination*, 229, pp. 1020.

World Bank , 2012. Renewable energy desalination: an emerging solution to close the water gap in the Middle East and North Africa (English). Water Partnership Program (WPP). Washington, DC: World Bank.

WRA , 2011a, Desalination Plant Intakes Impingement and Entrainment Impacts and Solutions, White Paper, the WaterReuse Association (WRA), Alexandria, Virginia, USA, June.

WRA , 2011b, Overview of Desalination Plant Intake Alternatives, White Paper, the WaterReuse Association (WRA), Alexandria, Virginia, USA, June.

WRRF , 2016, Database of Permitting Practices for Seawater Desalination Concentrate Disposal, WRRF-13-07, Mickley & Associates and Water Globe Consulting for Water Environment and Reuse Foundation (WRRF), IWA Publishing, Alexandria, Virginia.

Cost Estimates Types and Accuracy

Al-Bazedi, G. , El-Sayed, A. , Abdel-Fatah, M., 2016, Comparison between reverse osmosis desalination cost estimation trends, *Journal of Scientific and Engineering Research*, 3 (5), pp. 5662.

Bazargan, A. , Editor, 2018, A Multidisciplinary Introduction to Desalination, River Publishers, Denmark/The Netherlands.

Farrell, M.D. , Cimino, J. , 2003, Reverse Osmosis Desalination Cost Planning Model, *Proceedings of IDA World Congress on Desalination and Water Reuse Desalination: The Source of Sustainable Water Supplies*, Paradise Island, Bahamas, Sept. 28Oct. 3.

IAEA , 2000, Examining the Economics of Seawater Desalination Using the DEEP Code, International Atomic Energy Agency.

MEDRC , 2013, Toolbox of Graphic and Numeric Models for Estimating Costs of Seawater Reverse Osmosis Desalination Projects, Middle East Desalination Research Center (MEDRC) and Sustainable Water Integrated Management Support Mechanism (SWIM-SM), June.

Moch Jr., I. , 2002, A 21st century study of global seawater reverse osmosis operating and capital costs, Proceedings of IDA World Congress, Manama, Bahrain, March 813.

Moch Jr., I. , Querns, W. , Steward, D. , 2008, WT Cost II Modeling the Capital and Operating Costs of Thermal Desalination Processes Utilizing a Recently Developed Computer Program That Evaluates Membrane Desalting, Electrodialysis, and Ion Exchange Plants, Desalination and Water Purification Research and Development Program Report No. 130, US Department of the Interior, Bureau of Reclamation.

Pinto, F.S. , Marques, R.C. , 2017, Desalination project economic feasibility: A standardization of cost determinants, Renewable and Sustainable Energy Reviews, 78, pp. 904915.

Watson, I. , Morin, O. , Henthorne, L. , 2003, Desalting Handbook for Planners, 3rd Edition, Report No. 72, USBR, July.

World Bank , 2016, Cost of Desalination for Domestic Water Supply in the MENA Region, Prepared by Water Globe Consultants for the World Bank, November.

Capital Costs

Mackey, E.D. , Pozos, N. , James, W. , Seacord, T. , Hunt, H. , Mayer, D. , 2011, Assessing Seawater Intake Systems for Desalination Plants, Project #4080, Water Research Foundation, Denver, Colorado.

Voutchkov, N. , 2004a, Seawater desalination costs cut through power plant collocation, Filtration + Separation, September, pp. 2426.

Voutchkov, N. , 2004b, Thorough study is key to large beach well intakes, The Desalination and Water Reuse Quarterly, 14, pp. 1620.

Voutchkov, N. , 2011, Desalination Plant Concentrate Management, Water Treatment Academy, TechnoBiz Communications, Co., Ltd., Bangkok, Thailand.

Voutchkov, N. , 2013, Desalination Engineering Planning and Design, McGraw Hill, New York.

Voutchkov, N. , 2017, Pretreatment for Reverse Osmosis Desalination, Elsevier, Amsterdam, Oxford, Cambridge.

110 Watson, I. , Morin, O. , Henthorne, L. , 2003, Desalting Handbook for Planners, 3rd Edition, Report No. 72, USBR, July.

World Bank , 2016, Cost of Desalination for Domestic Water Supply in the MENA Region, Prepared by Water Globe Consultants for the World Bank, November.

Ziolkowska, J.R. , 2015, Is desalination affordable? Regional cost and price analysis, Water Resources Management, 29, pp. 13851397.

Operation and Maintenance Costs

Cotruvo, J. , Voutchkov, N. , Fawell, J. , Payment P. , Cunliff, D. , Lattemann, S. , 2010, Desalination Technology Health and Environmental Impacts, CRC Press, Taylor & Francis Group, Boca Raton, FL.

Elемеlech, M. , 2012, Seawater Desalination, Lecture presented at the 2012 NWRI Clarke Prize Conference, Newport Beach, California, November 2.

Lahav, O. , Voutchkov, N. , Birnhack, L. , 2012, Post-Treatment of Desalinated Water, Balaban Desalination Publications, Hopkinton, MA.

MacHarg, J. , Seacord, T.F. , Sessions, B. , 2008, ADC baseline tests reveal trends in membrane performance, Desalination and Water Reuse, 18/2, pp. 3039.

Seacord, T.F. , Coker, S.D. , MacHarg, J. , 2006, Affordable desalination collaboration 2005, Proceedings of the 2006 Biennial Conference & Exposition of the American Membrane Technology Association (AMTA), July 31August 2, Anaheim, California.

Voutchkov, N. , 2014, Desalination Engineering, Operation and Maintenance, McGraw Hill., Alexandria, VA.

Voutchkov, N. , 2017, Pretreatment for Reverse Osmosis Desalination, Elsevier, Amsterdam, Netherlands.

Water Production Cost

- Caldera, U. , Breyer, C. , 2017, Learning curve for seawater reverse osmosis desalination plants: Capital cost trend of the past, present and future, *Water Resources Research*, 53, pp. 116.
- Lapiente, E. , 2012, Full cost of desalination. A case study of the Segura River Basin, *Desalination*, 300, pp. 4055.
- Pinto, F.S. , Marques, R.C. , 2017, Desalination project economic feasibility: A standardization of cost determinants, *Renewable and Sustainable Energy Reviews*, 78, pp. 904915.

Project Implementation and Costs

- Ameyaw, E.E. , Chan, A.P.C. , Owusu-Manu, D. , Edwards, D.J. , Dartey, F. , 2017, A fuzzy-based evaluation of financial risks in build-own-operate-transfer water supply projects, *Journal of Infrastructure Systems*, 23, (4), pp. 113.
- Rebeiz, K.S. , 2012, Public-private partnership risk factors in emerging countries: BOOT illustrative project, *Journal of Management in Engineering*, 10.1061, ASCE, pp. 421428.
- Vining, A.R. , Boardman, A.E. , Poschmann, F. , 2005, Public-private partnerships in the US and Canada: There are no free lunches, *Journal of Comparative Policy Analysis*, 7 (3), pp. 199220.
- World Bank , 2014, *Water PPPs in Africa*, July 2014.

Cost Management

- Alkhudhiri, A. , Darwish, N. , Hilal, N. , 2012, Membrane distillation: A comprehensive review, *Desalination*, 287, pp. 218.
- AWWA , 2007, Voutchkov, N. , Bergman, R. , Chapter facility design and construction, in *Reverse Osmosis and Nanofiltration, Manual of Water Supply Practices M 46*, Second Edition.
- AWWA , 2011, Voutchkov, N. , Hunt, H. , Chapter environmental impacts and mitigation measures in *Desalination of Seawater, Manual of Water Supply Practices M 61*.
- Barrasi, G. , 2018, High recovery in SWRO using a multistage turbocharger configuration: Process optimization and cost analysis, *CaribDA 2018 Biennial Conference and Exposition*, May 29-June 1, 2018, Curacao.
- Bazargan, A. , Editor, 2018, *A Multidisciplinary Introduction to Desalination*, River Publishers, Denmark, Netherlands.
- Burn, S. , Gray, S. , 2016, *Efficient Desalination by Reverse Osmosis. A Guide to RO Practice*, IWA Publishing, London, UK.
- Choules, P. , Schrotter, J.C. , Lepar, J. , Gaid, K. , Lafon, D. , 2007, Reverse osmosis: Improved operation through experience with SWRO plants, Presented at the American Membrane Technology Associations Conference, Las Vegas, Nevada, July 23-26.
- Choules, P. , Ben Boudinar, M. , Mack, B. , 2009, Membrane (MF&UF) pre-treatment design and operational experience from three seawater RO plants, Presented at IDA World Congress Atlantis, The Palm Dubai, UAE November 7-12.
- Giwa, A. , Hasan, S.W. , Yousuf, A. , Chakraborty, S. , Johnson, D.J. , Hilal, N. , 2017, Biomimetic membranes: A critical review of recent progress, *Desalination*, 420, October 15, pp. 403424.
- Goosen, M.F.A. , Sablani, S.S. , Al-Hinai, H. , Al-Obeidani, S. , Al Belushi, R. , Jackson, D. , 2004, Fouling of reverse osmosis and ultrafiltration membranes: A critical review, *Separation Science and Technology*, 39(10), pp. 2261-2297.
- Gude, V.G. , 2016, *Desalination and sustainability: An appraisal and current perspective*, *Water Research*, 89, pp. 87106.
- 206 GWI , 2017, *IDA Desalination Yearbook 2017-2018*, Global Water Intelligence (GWI) and International Desalination Association (IDA), Media Analytics Ltd., Oxford, UK.

Hilal, N. , Wright, C.J. , 2018, Exploring the current state of play for cost-effective water treatment by membranes, *Nature Partner Journals*, 1: 8.

Kitamura, K. , Miyakawa, H. , 2017, Verification of advanced designed seawater RO system for low energy and operation cost, *The International Desalination Association World Congress* So Paulo, Brazil.

Knops, F. , Lintelo, R. , 2009, Long-term operating experience of Seaguard UF as pretreatment to SWRO, in the Mediterranean region, *Desalination and Water Treatment*, 5, pp. 7479.

Kurihara, M. , Takeuchi, H. , 2018, SWRO-PRO system in Mega-ton Water System for energy reduction and low environmental impact, *Water*, 10, 48.

Lan, J.M. , Campos, C. , Baudin, I. , Janex, M.L. , 2003, Understanding membrane fouling: A review of over a decade of research, *Water Science and Technology: Water Supply*, 3, (56), pp.155 164.

Leparc, J. , Rapenne, S. , Courties, C. , Lebaron, P. , Croue, J.P. , Jacquemet, V. , Turner, G. , 2007, Water quality and performance evaluation at seawater reverse osmosis plants through the use of advanced analytical tools, *Desalination*, 203, pp. 243255.

Mickols, W.E. , Busch, M. , Maeda, Y. , Tonner, J. , 2005, A novel design approach for seawater plants, *IDA World Congress*, Singapore.

Migliorini, G. , Luzzo, E. , 2004, Seawater reverse osmosis plant using the pressure exchanger for energy recovery: A calculation model, *Desalination*, 165, pp. 289298.

Mosset, A. , Bonnlye, V. , Petrya, M. , Sanz, M.A. , 2008, The sensitivity of SDI analysis: From RO feed water to raw water, *Desalination*, 222, pp. 1723.

Ng, H.Y. , Tay, K. G. , Chua, S. C. , Shea H. , 2008, Novel 16-inch spiral-wound RO Systems for Water Reclamation A Quantum Leap in Water Reclamation Technology, *Desalination*, 225, pp. 275287.

NRC , 2008, Desalination: A national perspective, committee on advancing desalination technology, Water Science and Technology Board, National Research Council (NRC) of the U.S. National Academies.

Passow, U. , 2002a, Transparent exopolymer particles (TEP) in aquatic environments, *Progress in Oceanography*, 55, pp. 287333.

Passow, U. , 2002b, Formation of transparent exopolymer particles, TEP, from dissolved precursor material, *Marine Ecology Progress Series*, 192, pp. 111.

Pearce, G.K. , 2007, The case of UF/MF pre-treatment to RO in seawater applications, *Desalination*, 203, pp. 286295.

Sommariva, C. , Al Hindi, M. , Fabbri, C. , 2009, Palm Jumeirah: The first large SWRO with ultra-filtration plant in the Gulf, Presented at the IDA World Congress Atlantis, The Palm Dubai, UAE November 712.

Stover, R.L. , 2005, The Galilah SWRO plant: An overview of the solutions adopted to minimize energy consumption, *Desalination*, 184, pp. 217221.

Shaw, M. , LeTurnea, T. , Liang, L.S. , Ng, K. , 2011, Low energy desalination: Siemens solution to global challenge, *IDA World Congress*, Perth, Australia.

Shahzad, M.W. , Burhan, M. , Ang, L. , Ng, K.C. , 2017, Energy-water-environment nexus underpinning future desalination sustainability, *Desalination*, 413, pp. 5264.

Stover, R. , N. Efraty , 2012, Low-energy Consumption with Closed Circuit Desalination, *IDA Journal*, Third Quarter, pp. 1219.

Tang, C.Y. , Zhao, Y. , Wang, R. , Helix-Nielsen, C. , Fane, A.G. , 2012, Desalination by biomimetic aquaporin membranes: Review of status and prospects, *Desalination*, 308, pp. 34pp. 40.

207 Villacorte, L.O. , Schurer, R. , Kennedy, M.D. , Amy, G. , Schippers, J.C. , 2009, Removal and deposition of transparent exopolymer particles (TEP) in Seawater UF-RO System, Presented at IDA World Congress Atlantis, The Palm Dubai, UAE November 712.

Voutchkov, N. , 2013, *Desalination Engineering: Planning and Design*, McGraw Hill.

Voutchkov, N. , 2011, *Desalination Plant Concentrate Management*, Water Treatment Academy, Division of TechnoBiz-Communications, Ltd.

Voutchkov, N. , 2017, *Pretreatment of Reverse Osmosis Desalination*, Elsevier, Oxford.

WRRF , 2013, Consideration of the co-siting of desalination facilities with municipal and industrial facilities, *WaterReuse Research Foundation (WRRF)*, Report No. WRRF-06-010D, Alexandria, Virginia, USA.

WRRF , 2016, *Database of Permitting Practices for Seawater Desalination Concentrate Disposal*, WRRF-13-07, Mickley & Associates and Water Globe Consulting for Water Environment and Reuse Foundation (WRRF), IWA Publishing, Alexandria, Virginia, USA.

Yiantsios, S.G. , Sioutopoulos, D. , Karabelas, A.J. , 2005, Colloidal fouling of RO membranes: An overview of key issues and efforts to develop improved prediction techniques, *Desalination*, 183, pp. 257272.208